

钢丝输送带生产线 成套橡胶机械 硫化机

产品名称	钢丝输送带生产线 成套橡胶机械 硫化机
公司名称	青岛金港湾机械公司
价格	.00/个
规格参数	额定排量:按实际 额定压力:16 品牌:金港湾
公司地址	中国 山东 青岛市 临港工业园188号
联系电话	86 0532 85185085 15806563897

产品详情

额定排量	按实际	额定压力	16
品牌	金港湾	型号	XLB
油箱容量	1200	柱数	框板式

产品名称：大型数控硫化机 产地：中国青岛 产品型号：xlb 规格参数：按合同

本产品配有自动温控、自动恒温、电机过载自动保护、工作板自动平衡装置

参数型号	xlb-1100*5700	xlb-1400*5700	xlb-1400*10000	xlb-1600*11600	xlb-1600*10000	xlb-2000*10000
热板规格	1100*5700	1400*5700	1400*10000	1600*11600	1600*10000	2000*10000
总压力	17.55mn	25.00mn	49.00mn	49.80mn	56.00mn	70.00mn
热板压力	2.8 mpa	3.13 mpa	3.5 mpa	3.3 mpa	3.5 mpa	3.5 mpa
柱塞直径	500 mm	360 mm	450 mm	450 mm	450 mm	600 mm
柱塞个数	5	10	20	20	18	16

柱塞行程	520 mm	400 mm	300 mm	300 mm	400 mm	300 mm
热板层数	2层	2层	1层	1层	2层	1层
夹持力	0.50	0.72	0.90	1.20	1.20	1.20
拉伸力	0.40	0.60	0.80	0.90	1.10	1.00
蒸汽压力	0.63 mpa	0.63 mpa	0.63 mpa	0.63 mpa	0.63 mpa	0.63 mpa
冷却压力	0.3 mpa	0.3 mpa	0.3 mpa	0.3 mpa	0.3 mpa	0.3 mpa
控制方式	plc	plc	plc	plc	plc	plc
用途	输送带	输送带	输送带	输送带	输送带	输送带

该机使用于硫化普通橡胶输送带、尼龙输送带/pvg输送带、钢丝绳输送带等织物芯平行胶带。主机为框式结构，热板及柱塞均为选用优质材料，加工精密，不易磨损，不易腐蚀，维修方便，工作压力稳定，调整方便。该机采用plc控制，硫化过程可实现多程序自动化控制，可自动检测和调节热板温度，提高了平板硫化机组控制水平，降低了劳动强度，提高了生产效率。

product name: large nc machine origin: chinese qingdao model: xlb specifications: according to the contract

this product is equipped with automatic temperature control, automatic constant temperature, motor overloaded know protection

parameter model xlb - 1100 * 57 xlb - 1,400 * 57 xlb - 1,400 * 10,000 xlb - 16 11600 * xlb - 1600 * 10,000 xlb - 2000 * 10,000

hot plate specifications 1100 * 57 14 * 57 14 * 10,000 16 11600 * 16 * 10,000 2000 * 10,000

total pressure 17.55 mn 25.00 mn 49.00 mn 49.80 mn 56.00 mn 70.00 being mn

hot plate stress 2.8 mpa 3.13 mpa 350 mpa 3.3 mpa 350 mpa 350 mpa

diameter of piston 500 mm 360 mm 45 mm 45 mm 45 mm 600 mm

number of plunger 5 10 20 20 18 16

piston stroke 520 mm 400 mm 300 mm 300 mm 400 mm 300 mm

hot plate layer 2 layer 2 1 layer 2 1

clamping force 0.5 0.7 2.0 9.0 1.2 0.1 2.0 1.2 0

tensile strength 0.4 0.6 0.8 0.9 0.1 1.0 1.0 0

the steam pressure 0.63 mpa 0.63 mpa 0.63 mpa 0.63 mpa 0.63 mpa 0.63 mpa

cooling pressure 0.3 mpa 0.3 mpa 0.3 mpa 0.3 mpa 0.3 mpa 0.3 mpa

control mode plc plc plc plc plc plc

by way belt belt belt belt belt belt the ordinary rubber vulcanization used in belt conveyor, nylon rope belt conveyor, pvc/fabric such as core parallel tape. host for frame structure, the hot plate and piston are using high quality materials and the processing precision, easy wear and corrosion, convenient maintenance, working pressure stability, convenient adjustment. this machine adopts plc control, vulcanization process can achieve more procedure control, automation automatic detection and adjusting temperature of the hot plate, improving the curing press control level, reduce the labor intensity, improve the production efficiency.