

Coriolis mass flowmeter

| | |
|------|-----------------------------|
| 产品名称 | Coriolis mass flowmeter |
| 公司名称 | 上海中隆实业有限公司 |
| 价格 | 9800.00/套 |
| 规格参数 | 品牌:中隆 型号:LK 类型:质量流量计 |
| 公司地址 | 中国 上海市 上海市浦东新区长岛路1203弄21号 |
| 联系电话 | 86 021 50250324 13917058589 |

产品详情

| | | | |
|------|--|------|---------------------------------------|
| 品牌 | 中隆 | 型号 | LK |
| 类型 | 质量流量计 | 测量范围 | 0.003-800t/h (m3/h) |
| 精度等级 | 0.15% | 公称通径 | 3-250 (mm) |
| 适用介质 | Liquid Compressed gas | 工作压力 | 4 (40Must have custom-made) (MPa) |
| 工作温度 | -60--200 (Other must have custom-made) () | | |

technical indicators

liquid flow performance

traffic measurement error: $= e_i\% * \text{flow} + e_0$, measurement accuracy $e = \pm [(\quad / \text{traffic}) \times 100]\%$ 。

| type | size(mm) | flow range | accuracy rating(ei) | 0:00 instability(e0) |
|------|-----------|------------|---------------------|----------------------|
| k-06 | 6 | 0-0.8t/h | 0.15 | 0.00010t/h |
| k-10 | 10 | 0-1.5 t/h | 0.15 | 0.00017t/h |
| k-15 | 15 | 0-3 t/h | 0.15 | 0.00027t/h |
| k-20 | 20 | 0-7 t/h | 0.15 | 0.0006 t/h |

| | | | | |
|-------|-----|-----------|------|------------|
| k-25 | 25 | 0-12 t/h | 0.15 | 0.0009 t/h |
| k-32 | 32 | 0-21 t/h | 0.15 | 0.0014 t/h |
| k-40 | 40 | 0-36 t/h | 0.15 | 0.0025 t/h |
| k-50 | 50 | 0-60 t/h | 0.15 | 0.0041 t/h |
| k-80 | 80 | 0-150 t/h | 0.15 | 0.013 t/h |
| k-100 | 100 | 0-240 t/h | 0.15 | 0.025 t/h |
| k-150 | 150 | 0-450 t/h | 0.15 | 0.069 t/h |

error flow table

density performance index (liquid only)

precision $\pm 0.002\text{g/cm}^3$

energy consumption

lb112 the sensor-equipped with the most 18w

temperature performance

precision ± 1

media measured temperature $-60 \sim +200$ ($-200 \sim +360$ needs inspecial made)

the use of ambient temperature $-60 \sim +80$

pressure level

traffic pressure level 4mpa (in 40mpa needs inspecial made)

structural materials

measuring tube 316l (others body's needs inspecial made)

shell 304

junction box aluminium

seeks the proxy : fhtdlzl@188.com