

VOIP网关HT503|双口网关|

产品名称	VOIP网关HT503 双口网关
公司名称	青岛畅信达通信有限公司
价格	380.00/件
规格参数	品牌:潮流 型号:HT503 设备类型:VOIP
公司地址	山东省青岛市市北区上清路12号北A1#-201室
联系电话	0532-82754222

产品详情

品牌	潮流	型号	HT503
设备类型	VOIP	接口	电话头

handytone ht-502

ht-503是基于sip2.0标准的双口模拟电话适配器，双10m/100mbps以太网口并内置高性能nat路由器，网口状态和信息等待led，还带底座使该设备能竖起来放置。ht-503支持普遍的即插即用的特点，可注册两个帐号平台，为您提供传统和高级的通话功能

ht503提供加强型安全等级，在任何通话中使用对称性和非对称性语音编码/rtp完成自动系统配置，并且支持大部分常用的语音编码。

功能&性能

luniversal plug-in-play (upnp)

l1个fxs接口1个fxo接口(rj11) w/可以使用2个sip帐号平台

l双10/100 mpbs网口(rj45)/内置路由

l高级功能:

-来电显示,呼叫等待,三方会议,呼叫前转和后转-呼叫转移,请勿打扰,语音邮件, mls语音应答-t.38传真,可调整性拨号计划, ip直接呼叫

I支持以下语音编码:

-g.711(a/u-law), g.723.1, g.729a/b, g.729e-g.726-40/32/24/16以及ilbc

It.38传真

Itp/https/telnet/tftp系统配置

Isip over tcp/tls

I使用电话和传真时通过ip连接

I通过web简单配置进行管理和安装

I提供传统和高级的电话功能

I便携式设计可在家里或路上使用

功能特性	ht-502
以太网接口	2 rj45 (lan/wan)
nat/router	yes
dhcp	client/server
fxsport	2
fxoport	no
pstn透传接口	no
语音邮件显示	yes
语音编码	g.711(a/?law), ilbc, g.723, g.729a/b/e, g.726, t.38(fax)
远程配置	tftp/http

硬件指标

电话接口	2 fxs接口, 2个sip帐号
网络接口	双10m/100 mbps, rj-45
led指示灯	电源, wan, lan, phone1 and phone2
出厂设置键	恢复出厂设置按键
voice over packet capabilities	voice activity detection (vad) with cng (comfort noise generation) and plc (packet loss concealment), dynamic jitter buffer, modem detection & auto-switch to g.711, packetized voice protocol unit (supports rtp/rtcp and aal2 protocol), g.168 compliant echo cancellation, lec (line echo cancellation) with nlp
voice compression	g.711 + annex i (plc), annex ii (vad/cng format) encoder and decoder, g.723.1a, g.726(adpcm), g.729a/b/e, ilbc g.726 provides proprietary vad, cng, and signal power estimation voice play out unit (reordering, fixed and adaptive jitter buffer, clock synchronization), agc (automatic gain control), status output, decoder controlling via voice packet header

dhcp服务器端/客户端	yes, nat router or switched mode
ip传真	t.38 compliant group 3 fax relay up to 14.4kpbs and auto-switch to g.711 for fax pass-through (pending), fax datapump v.17, v.19, v.27ter, v.29 for t.38 fax relay
qos	diffserve, tos, 802.1 p/q vlan tagging
ip传输	rtp/rtcp
dtmf方案	flexible dtmf transmission method, user interface of in-audio, rfc2833, and/or sip info
ip信令	sip (rfc 3261)
保存	tftp, http, https (pending)
控制	tls/sips
管理	syslog support, https and telnet (pending), remote management using web browser, auto/manual provisioning system support layer 2 (802.1q, vlan, 802.1p), layer 3 qos (tos, diffserve, mpls)
电源	output: 12vdc / input: 100-240 vac/50-60 hz
环境湿度	operational: 32 ° -104 ° f or 0 ° -40 ° c storage: 10 ° -130 ° f / humidity: 10-90% non-condensing
尺寸 (h x w x d)	25mmx 115mm x 75mm (when laying flat); 115mm x 25mm x 75mm (standing up)
short & long haul	ren3: up to150 ft on 24 awg line
呼叫功能	caller id display or block, call waiting caller id, call waiting/flash, call transfer, hold, forward, mute, 3-way conferencing
号码显示	bellcore type 1 & 2, etsi, bt, ntt, and dtmf-based cid
极性反转/闪烁	yes
emc	en55022/en55024 and fcc part15 class b
安全标准	ul