

ELO触摸屏ELO4200L ET3200L ET4600L触摸显示器

产品名称	ELO触摸屏ELO4200L ET3200L ET4600L触摸显示器
公司名称	上海亘圣电子科技有限公司客户部
价格	25700.00/台
规格参数	品牌:EL TOUCH 型号:ET4200L 类型:触控一体机
公司地址	中国 上海市闵行区 上海虹梅路269号
联系电话	86 021 34551793-802 13564184385

产品详情

品牌	ELO TOUCH	型号	ET4200L
类型	触控一体机	屏幕类型	液晶
屏幕尺寸	42寸 (寸)	分辨率	1920 × 1080
透光率	大于95% (%)		

4200L 42" interactive digital signage touch display model 4200L

useful screen area horizontal: 36.6" (930 mm); vertical: 20.6" (523 mm) monitor dimensions width: 40.2" (1020 mm); depth: 5.2" (132 mm); height: 24.1" (613 mm) (without stand) touch technology zero-bezel acoustic pulse recognition (apr) speakers a pair of 10 w stereo speakers facing down (in landscape mode) audio input connector 3.5 mm trs jack audio input signal range 1 vrms max stereo signal (standard pc line out) headphone output connector 3.5 mm trs jack headphone output signal delivers 90 mw of power into a 32 ohm stereo load (for 1 khz signal) lcd technology active matrix tft lcd diagonal size 42" aspect ratio 16:9 on-screen display (osd) controls: menu, up, down, select; settings: brightness, contrast, clock, phase, auto-adjust, h-position, v-position; maintain aspect ratio, sharpness, color temperature, osd timeout, osd language, mounting, osd h-position, osd v-position, volume, mute, recall defaults, video source, audio source; languages: english, french, italian, german, spanish, simplified chinese, traditional chinese, japanese; lockouts: osd, power; accessible through switches on the rear, or through the standard elo osd control box. stand options optional stand available, order part number e448725 mounting options vesa mis-f, 600 x 400, y, 6, 90 native (optimal) resolution 1920 x 1080 other supported resolutions 640 x 480 at 60 hz; 720 x 480 at 60 hz; 720 x 576 50 hz; 800 x 600 at 56, 60 hz; 1024 x 768 at 60 hz; 1280 x 720 at 50, 60 hz; 1280 x 960 at 60 hz; 1280 x 1024 at 60 hz; 1360 x 768 at 60 hz; 1366 x 768 at 60 hz; 1440 x 900 at 60 hz; 1680 x 1050 at 60 hz; 1920 x 1080 at 50, 60 hz colors 16.7 million brightness (typical) lcd panel: 700 nits; with apr: 600 nits response time (tr + tf) 6.5 msec total (typical) viewing angle (typical) horizontal: ± 89 ° or 178 ° total; vertical: ± 89 ° or 178 ° total contrast ratio (typical) 3500:1 input video format analog vga, hdmi 1.3 input video signal connector female de-15 for analog vga; hdmi type a receptacle for hdmi input frequency horizontal: 32-80 khz; vertical: 47-61 hz power supply internal ac input voltage 100-240 vac,

50/60 hz power connector iec 60320 c14 power consumption (typical) monitor only: on, max. audio, 100 v/60 hz: 230 w; sleep, 100 v/60 hz: 12.5 w; off, 100 v/60 hz: 11.5 w temperature operating: 0 ° c to 40 ° c (32 ° f to 104 ° f); storage: -20 ° c to 50 ° c (-4 ° f to 122 ° f) humidity (non-condensing) operating: 20-80%; storage: 10-90% weight actual: w/o computer module: 74.7 lb (33.9 kg); with computer module: 80.5 lb (36.5 kg) shipping 99.7 lb (45.2 kg) (computer module shipped separately) shipping box dimensions width: 47.0" (1194 mm); depth: 12.0" (305 mm); height: 31.0" (788 mm) warranty 3 years backlight lamp life (typical) 50,000 hours to half-brightness mtbf 50,000 hours demonstrated agency approvals argentina s-mark; australia c-tick; canada cul; china ccc; mexico nom; russia & cis gost; united states ul; elo declarations; europe ce; canada ic; japan vcc; united states fcc

4600I 46" interactive digital signage touch display model 4600I

useful screen area horizontal: 40.1" (1018 mm); vertical: 22.5" (573 mm) monitor dimensions width: 44.1" (1120 mm); depth: 5.3" (135 mm); height: 26.1" (664 mm) (without stand) touch technology zero-bezel acoustic pulse recognition (apr) speakers a pair of 10 w stereo speakers facing down (in landscape mode) audio input connector 3.5 mm trs jack audio input signal range 1 vrms max stereo signal (standard pc line out) headphone output connector 3.5 mm trs jack headphone output signal delivers 90 mw of power into a 32 ohm stereo load (for 1 khz signal) lcd technology active matrix tft lcd diagonal size 46" aspect ratio 16:9 on-screen display (osd) controls: menu, up, down, select; settings: brightness, contrast, clock, phase, auto-adjust, h-position, v-position; maintain aspect ratio, sharpness, color temperature, osd timeout, osd language, mounting, osd h-position, osd v-position, volume, mute, recall defaults, video source, audio source; languages: english, french, italian, german, spanish, simplified chinese, traditional chinese, japanese; lockouts: osd, power; accessible through switches on the rear, or through the standard elo osd control box. stand options optional stand available, order part number e448725 mounting options vesa mis-f, 600 x 200, y, 6, 90 native (optimal) resolution 1920 x 1080 other supported resolutions 640 x 480 at 60 hz; 720 x 480 at 60 hz; 720 x 576 50 hz; 800 x 600 at 56, 60 hz; 1024 x 768 at 60 hz; 1280 x 720 at 50, 60 hz; 1280 x 960 at 60 hz; 1280 x 1024 at 60 hz; 1360 x 768 at 60 hz; 1366 x 768 at 60 hz; 1440 x 900 at 60 hz; 1680 x 1050 at 60 hz; 1920 x 1080 at 50, 60 hz colors 16.7 million brightness (typical) lcd panel: 450 nits; with apr: 405 nits response time (tr + tf) 16 ms total (typical) viewing angle (typical) horizontal: ± 89 ° or 178 ° total; vertical: ± 89 ° or 178 ° total contrast ratio (typical) 3500:1 input video format analog vga, hdmi 1.3 input video signal connector female de-15 for analog vga; hdmi type a receptacle for hdmi input frequency horizontal: 32-80 khz; vertical: 48-62 hz power supply internal ac input voltage 100-240 vac, 50/60 hz power connector iec 60320 c14 power consumption (typical) monitor only: on, max. audio, 100 v/60 hz: 234 w; sleep, 100 v/60 hz: 12.5 w; off, 100 v/60 hz: 11.5 w temperature operating: 0 ° c to 40 ° c (32 ° f to 104 ° f); storage: -20 ° c to 50 ° c (-4 ° f to 122 ° f) humidity (non-condensing) operating: 20-80%; storage: 10-90% weight actual: without computer module: 82.1 lb (37.2 kg); with computer module: 87.7 lb (39.8 kg) shipping 110.2 lb (50.0 kg) (computer module shipped separately) shipping box dimensions width: 47.0" (1194 mm); depth: 12.0" (305 mm); height: 31.0" (788 mm) warranty 3 years backlight lamp life (typical) 50,000 hours to half-brightness mtbf 50,000 hours demonstrated agency approvals argentina s-mark; australia c-tick; canada cul; china ccc; mexico nom; russia & cis gost; united states ul; elo declarations; europe ce; canada ic; japan vcc; united states fcc

更多产品及问题请来电咨询谢谢！！ 赵磊：13564184385 13818841821