

Sliontec UV膜 6360-25

产品名称	Sliontec UV膜 6360-25
公司名称	厦门良厦贸易有限公司
价格	.00/个
规格参数	
公司地址	中国（福建）自由贸易试验区厦门片区中埔社10190号（注册地址）
联系电话	0592-6013840 15396145919

产品详情

UV DicingTape:No.6360-25

High adhesion

Feature:

Non-PVC backing is used

High-Pressure mercury lamp or black light can be used as lightsource

Isotropic performance at expanding process

Property:

Item No.	No.6360-25	
Color	Tape(PO)	Translucent
	Liner	Transparent
Thickness (um)	Backing	150
Liner:38um	Adhesive	10
Peelstrength	SUS	3.40(0.22)
[N/10mm] () :After UV	Glass	3.80(0.23)
	SI wafer	3.80(0.23)
Holding Power	40 /24hour	< 0.1mm
Tensile Strength (Before UV)		30/30
(TD/MD) (N/10mm)		
Elongation (Before UV)		910/840
(TD/MD) (%/10mm)		

UV irradiation condition : High-pressure mercury lamp, 75mW/cm² at 365nm, for 4 sec (300mJ/cm²)

Peel Strength (90 Peel) : Pass the 2kg roller in each direction at a rate of 300mm/min. Aging time ; 20min. Rate of peel ; 300mm/min.

Holding power : Pass the 2kg roller in each direction at a rate of 300mm/min. Load ; 1kg/25mm × 25mm

TD : Transverse Direction, MD : Machine Direction