

dn	50	65	80	100	125	150	200	250	300	350	400
l	230	290	310	350	400	480	600	730	850	980	1100
h	410	445	480	525	545	615	780	950	1120	1250	1380
d0	200	250	250	300	350	350	400	450	500	600	600
wt	24	30	41	56	90	98	170	350	502	560	750
ansi 300lb											
nps	2	2 1/2	3	4	5	6	8	10	12	14	16
l	267	292	318	356	400	444	559	622	711	762	864
h	400	440	465	565	615	715	930	1010	1230	1450	1645
d0	200	250	300	350	400	450	500	500	500	600	600
wt	25	30	35	56	96	120	212	330	472	715	920
gb 2.5mpa											
dn	50	65	80	100	125	150	200	250	300	350	400
l	230	290	310	350	400	480	600	730	850	980	1100
h	410	445	480	525	545	615	780	950	1120	1250	1380
d0	240	280	320	360	400	400	450	450	500	600	600
wt	24	30	42	58	90	98	170	350	502	560	750
gb 4.0mpa											
dn	50	65	80	100	125	150	200	250	300	350	400
l	230	290	310	350	400	480	600	730	850	980	1100
h	410	445	480	525	545	690	830	975	1120	1300	1425
d0	240	280	320	360	400	450	560	640	720	800	900
wt	24	30	42	58	90	125	173	491	705	930	1234

设计与制造标准：

设计与制造：bs1873 bs5160 gb12233 法兰尺寸：ansib16.5 jb/t79
gb9113 压力温度：ansib16.34 结构长度：ansib16.10 bs1873
gb12221 对焊连接尺寸：ansib16.25 检验与实验：bs6755 gb/t13927

安装尺寸及重量：

ansi 600lb												
nps	2	2 1/2	3	4	5	6	8	10	12	14	16	
l	292	330	356	432	508	559	660	787	838	889	991	
h	430	480	530	650	750	850	1050	1255	1470	1625	1815	
d0	200	250	250	350	350	450	500	600	680	760	760	
wt	35	50	60	110	200	230	410	625	860	1300	1590	
gb 6.4mpa						gb 10.0mpa						
dn	50	65	80	100	125	150	50	65	80	100	125	150
l	300	340	380	430	500	550	300	340	380	430	500	550
h	430	485	530	660	690	715	430	485	530	660	760	850
d0	280	320	360	450	450	450	280	320	360	450	450	450
wt	38	56	71	129	143	157	38	56	71	129	200	230
ansi 900lb												
nps	2			2 1/2			3			4		
l	372			422			384			460		
h	546			597			711			718		
d0	320			360			440			500		
wt	65			81			114			214		

gb 16.0mpa				
dn	50	65	80	100
l	300	340	380	430
h	430	570	605	710
d0	320	320	360	450
wt	45	75	105	165

j5/941h/y铸钢直通式截止（节流）阀

设计与制造标准：

设计与制造：bs1873 bs5160 gb12233 法兰尺寸：ansib16.5 jb/t79
 gb9113 压力温度：ansib16.34 结构长度：ansib16.10 bs1873
 gb12221 对焊连接尺寸：ansib16.25 检验与实验：bs6755 gb/t13927

安装尺寸及重量：

	ansi 150lb		ansi 300lb		ansi 600lb				ansi 900lb				
nps	16	18	14	16	8	10	12	14	16	3		4	
l	914	978	762	864	660	787	838	889	991	384		460	
h	1270	1300	1450	1645	1050	1255	1470	1625	1815	711		718	
d0	600	700	600	600	500	600	680	760	760	440		500	
wt	760	1050	715	920	410	625	860	1300	1590	114		214	
	3500	3500	2500	3500	2500	2500	3500	5000	5000	1000		1200	
	gb 1.6mpa		gb 2.5mpa		gb 4.0mpa		gb 6.4mpa		gb 10.0mpa		gb 16.0mpa		
dn	250	300	250	300	200	200	150	200	80	100	125	150	200
l	650	750	650	750	600	650	550	650	380	430	500	550	650
h	1140	1230	1160	1230	1160	1220	1240	1430	820	935	1180	1290	1495
d0	450	500	450	500	400	500	500	550	400	450	500	550	650
wt	550	785	585	795	399	420	450	850	216	238	490	674	111

														2
	1000	1200	1500	1800	1200	1800	1800	2500	1000	1200	1500	1800	2	0
													2	5
													0	0

注：h、wt为电动形式的参考数据。 为伞齿轮、电动装置的参考力矩，单位nm。