安陆市涤纶纤维粉尘爆炸检测 爆炸指数鉴定

产品名称	安陆市涤纶纤维粉尘爆炸检测 爆炸指数鉴定
公司名称	江苏广分检测技术有限公司销售部
价格	.00/个
规格参数	涤纶纤维粉尘:爆炸指数鉴定 周期:5-7天 检测范围:全国
公司地址	江苏省昆山市陆家镇星圃路12号智汇新城B区7栋
联系电话	0512-65587132 13906137644

产品详情

e of dust cloud）、粉尘层着火温度（Minimum Ignition Temperature of dust layer）、粉尘云极限氧浓度（Limiting Oxygen Concentration）

粉尘爆炸检测项目

粉尘爆炸，粉尘爆炸可爆性筛选、粉尘云爆炸压力、粉尘云爆炸压力上升速率（Maximum rate of explosion pressure rise）、爆炸指数（Explosion index）、粉尘云最小爆炸浓度（Minimum Explosion Concentration）、也称：爆炸下限（LEL, Lower Explosion Limit）、粉尘云最小点火能量（Minimum Ignition Energy）、粉尘云着火温度（Minimum Ignition Temperature of dust cloud）、粉尘层着火温度（Minimum Ignition Temperature of dust layer）、粉尘云极限氧浓度（Limiting Oxygen Concentration）。

粉尘爆炸检测标准

粉尘爆炸检测参考标准

GB/T 粉尘云爆炸压力和爆炸指数测定方法

ISO 6184/1-1985 Determination of explosion indices of combustible dusts in air

BS EN 14034-1:2004 Determination of the maximum explosion pressure Pmax of dust clouds

BS EN 14034-2:2006 Determination of the maximum rate of explosion pressure (dp/dt)max of dust clouds

ASTM E 1226-10 Standard test method for explosibility of dust clouds

GB/T 粉尘云爆炸下限浓度测定方法

BS EN 14034-3:2006 Determination of the lower explosion limit LEL of dust clouds

ASTM E 1515-07 Standard test method for minimum explosible concentration of combustible dusts

GB/T 粉尘云最小着火能量测定方法

IEC 61241-2-3-1994 Test methods Section 3 Method for determining minimum ignition energy of dust air mixtures

BS EN Determination of minimum ignition energy of dust/air mixtures

ASTM E 2019-03(2007) Standard test method for minimum ignition energy of a dust cloud in air

GB/T 粉尘云着火温度测定方法

IEC 61241-2-1:1994 Test methods Section 1 Methods for determining the minimum ignition temperatures of dust

BS EN 50281-2-1:1999 Electrical apparatus for use in the presence of combustible dust-Part 2-1: Test methods-Methods of determining minimum ignition temperatures

ASTM E 1491-06 Standard test method for minimum autoignition temperature of dust clouds

GB/T 粉尘层着火温度测定方法

ASTM E 2021-09 Standard test method for hot surface ignition temperature of dust layer