

高刚性导电PC 日本帝人 B-7330R

产品名称	高刚性导电PC 日本帝人 B-7330R
公司名称	东莞市樟木头常虹塑胶原料经营部
价格	.00/个
规格参数	性能:高刚性导电 型号:B-7330R 3:物性参数
公司地址	东莞市樟木头镇百果洞新城街二巷六号
联系电话	13688946070

产品详情

高刚性导电PC 日本帝人 B-7330R

日本帝人Panlite PC聚碳酸酯：EN-8515N、EN-8615N 阻燃抗静电ML-1105 高光扩散级

ML-1103 光扩散 标准

ML-1102 光扩散 高光透过

LN-3010RM 光反射 扩散级 阻燃级LD-1000RM 光反射 扩散级 半透LN-2525ZA 难燃级 半透明 耐候级

Lexan 4504 High heat resistant PC copolymer, WITH DTUL OF 290F AT 264 psi. Lexan 4704 High heat polycarbonate copolymer, with DTUL of 300F at 264 psi. Lexan HF1140 Ideal for disposables/short life cycles. Lexan HF1140R High flow grade. Heat stabilized. Enhanced level of mold release. Lexan OQ4120R Optical grade with UV cut-off up to 400 nm, greater optical purity than standard grades. Lexan OQ4320R Optical grade with UV cut-off up to 400 nm; greater optical purity than standard grades. Lexan OQ4620R Optical grade with UV cut-off up to 400 nm, greater optical purity than standard grades. Lexan OQ2720 Ophthalmic/safety lens market. OQ2xxx series in all transparent tints. Lexan 3412ECR Lexan* 3412ECR Polycarbonate (PC) resin is a 20% glass fiber filled