

			2	0				6					3							5					
	12.5~25	22	20	65	13	155	90	11	17.6	60	12	145	90	72.	40	30	22	25	7	25	22	14	15.	4	4.2
			2	0					6					3								14	15.	4	4.2
	12.5~10	28	26	90	14	170	12	11	23.1	70	15	170	110	87	45	35	28	31	7	30	27	16	18	5	5.5
	0		5	0			0		1																
	100~20	32	30	13	17	210	16	13	30.2	75	18	204	130	99.	55	45	32	36.5	10	30	27	19	21	5	16
	0		2	0	0		7		2					8											
0.75kw	12.5~25	28	26	90	14	170	12	11	23.1	70	15	170	110	87	45	35	28	31	7	30	27	16	18	5	6.5
			5	0			0		1																
	30~120	32	30	13	17	210	16	13	30.2	75	18	204	130	99.	55	45	32	36.5	10	30	27	19	21	5	19.5
			2	0	0		7		2					8											
	120~20	40	36	15	21	260	20	18	37.9	96	23	252	160	122	65	55	40	44	12	35	32	24	27	7	38
	0		3	0	0		0		6																
1.5kw	5~30	32	30	13	17	210	16	13	30.2	75	18	204	130	99.	55	45	32	36.5	10	30	27	19	21	5	19.5
			2	0	0		7		2					8											
	40~100	40	36	15	21	260	20	18	37.9	96	23	252	160	122	65	55	40	44	12	35	32	24	27	7	38
			3	0	0		0		6																
	120~20	50	38	16	23	285	21	18	39.2	10	25	305	200	149	75	65	50	53.5	14	45	42	28	31	8	51.2
	0		2	0	0		0			4															
2.2kw	5~10	32	30	13	17	210	16	13	30.2	75	18	204	130	99.	55	45	32	36.5	10	30	27	19	21	5	20.5
			2	0	0		7		2					8											
	15~60	40	36	15	21	260	20	18	37.9	96	23	252	160	122	65	55	40	44	12	35	32	24	27	7	39
			3	0	0		0		6																
	75~120	50	38	16	23	285	21	18	39.2	10	25	305	200	149	75	65	50	53.5	14	45	42	28	31	8	53
			2	0	0		0			4															
3.7kw	5~20	40	36	15	21	260	20	18	37.9	96	23	252	160	122	65	55	40	44	12	35	32	24	27	7	39
			3	0	0		0		6																
	25~100	50	38	16	23	285	21	18	39.2	10	25	305	200	149	75	65	50	53.5	14	45	42	28	31	8	53
			2	0	0		0			4															

1. 浅蓝色为轻扭力之机型 2. 40~50筒齿箱上附加o型吊环(高度约50mm)