

4.5M三节全自由门架 四轮内燃平衡重式叉车

产品名称	4.5M三节全自由门架 四轮内燃平衡重式叉车
公司名称	浙江华和叉车有限公司
价格	.00/个
规格参数	额定起重量:3500 (kg) 耗能方式:燃料叉车 型号:HH35
公司地址	浙江省台州市路桥区金清镇
联系电话	18539573022

产品详情

额定起重量	3500 (kg)	耗能方式	燃料叉车
型号	hh35	货叉长度	1070 (mm)
载重量	3500 (kg)	货叉最低位	150 (mm)
行走方式	内燃式叉车	工业车辆	集装箱叉车
特种行业	集装箱行走吊		

结构特点：动力性、经济性以及舒适性

structure characteristics: powerful, economical and comfortable

座椅：座椅前后可以移动，并根据人的体重自动调整座椅承载能力，提高了驾驶员的操作舒适性。配备座椅安全带，有助于驾驶员的行车安全性。

Is eat: seat could be adjusted back and forth. the loading capacity of the seat can be automatically according to body weight, thereby to make operation comofortable. safety belt is equipped to ensure driver ' s safety.

货叉下降缓冲系统: 货叉下降即将接触地面时，货叉逐渐减缓下降速度，减少碰撞并可降低噪音。

Ifork buffer system: when the forks are landing to touch ground, it will speed down to reduce impact and noise.

ø 悬浮式车体 suspension vehicle body ø 人性化操作 humanism operation interface ø 门架智能缓冲 mast buffer system ø 液力车电子换挡 hydraulic electronic shifting ø 减震高级座椅 suspension seat ø 倒车照明灯 backup light

概	产地	origin	zhejiang huahe forklift company
---	----	--------	---------------------------------

要	型号model			hh35z	
	动力形式power type			柴油diesel	
	额定载荷rated capacity		kg	3500	
	载荷中心距load center		mm	500	
尺寸	起升高度lift height		mm	3000	
	自由起升高度free lift height		mm	130	
	货叉尺寸fork size		n*u*l	mm	1070*125*
	门架倾角mast inclination		front/back	deg	6/12
	前悬距front overhang			mm	490
	外形尺寸 overall dimensions	总长length to face of fork		mm	2730
		总宽overall width		mm	1225
		门架不起升高度 mast lowered height		mm	2095
		安全架高度 overhead guard height		mm	2120
	最小转弯半径turning radius			mm	2200
	最小直角通道宽度min. right angle aisle width			mm	2105

性能	行驶速度travel speed		no load	km/h	9/20
			full load	mm/s	8.8/18.5
	无载最大起升速度lift speed			mm/s	480
	最大爬坡度max. gradeability			%	20
	最大牵引力max. drawbar pull			kn	13
	自重self weight			kg	4700
轮胎	轮胎tires		前轮front		28*9-12-1
			后轮rear		6.50-10-10
	轮距tread		前轮front	mm	1000
			后轮rear	mm	970
	轴距wheelbase			mm	1700
	最小离地间隙(空载/满载) min. ground (no load/full load)		门架mast	mm	152/132
		车架frame	mm	158/138	
动力与传动	蓄电池battery	电压voltage		v/ah	12/90
	发动机engine	型号model			3.5t
		产地origin			chinese
		额定功率rated output/r.p.m		kw/r.p.m	37/2650

额定扭距rated torque		n.m/r.p.m	148/1800
汽缸数no.cylinder			4
排量displacement		cc	2540
类型type			液力hydr
档位shift	前后(fwd/rwd)		1/1
工作压力operating pressure		mpa	17.5