

防爆断路器BDZ51-32/3,隆迈防爆

产品名称	防爆断路器BDZ51-32/3,隆迈防爆
公司名称	浙江隆迈防爆电气有限公司
价格	180.00/台
规格参数	
公司地址	浙江省温州市乐清市柳市镇金丝河村（注册地址）
联系电话	18367862323

产品详情

bdz51- 防爆断路器(b)bdz51- explosion-proof circuit breaker (b)1. 爆炸性气体环境危险场所：1区、2区；2. 可燃性气体、蒸气级别： a、 b；3. 温度组别：t1~t4；4. 户内、户外(ip54)。1. for the dangerous sites with explosion division;2. flammable gas, steam class : a、 b;3. temperatures classification : t1~t6;4. indoor and outdoor(ip54).1. diecasted al-alloy shell with sprayed surface;2. inside mounted c45n、 45ad、 nm10、 dz20 series circuit breaker;3. possessing the guarding function against overcurrent, overload, short-circuit, etc;4. steel pipe and cable wiring.1. 铸铝合金外壳，表面喷塑；2. 内装c45n、 c45ad、 nm10、 dz20 系列断路器；3. 具有过载、短路等保护功能；4. 钢管或电缆布线。额定电压ratedvoltage (v)额定电流ratedcurrent (a)防爆标志explosion-proofing marker防护等级protectioncategory防腐等级corrosion-proofing grade进线口螺纹inlet"sthread电缆外径(mm)cable's outside diameter380/2201, 3, 5, 10, 15, 20,25, 32, 40, 50, 63exde bt4exd bt4ip54w, wf1, wf2g3/4 10~ 15g1 12~ 18额定电压ratedvoltage (v)额定电流ratedcurrent (a)防爆标志explosion-proofing marker防护等级protectioncategory防腐等级corrosion-proofing grade进线口螺纹inlet"sthread电缆外径(mm)cable's outside diameter380/2201, 3, 5, 10, 15, 20,25, 32, 40, 50, 63exde bt4exd bt4ip54w, wf1, wf2g3/4 10~ 15g1 12~ 18g11/4 13~ 23g11/2 17~ 26额定电压ratedvoltage (v)额定电流ratedcurrent (a)防爆标志explosion-proofing marker防护等级protectioncategory防腐等级corrosion-proofing grade进线口螺纹inlet"sthread电缆外径(mm)cable's outside diameter32, 40,50, 63, 80, 100exde bt4exd bt4ip54w, wf1, wf2g1 12~ 18g11/4 15~ 22g11/2 20~ 26g2 27~ 371. 铸铝内装nm1、 dz20系列断路器；3. 具有过载、短路等保护功能；4. 钢管或电缆布线。1. diecasted al-alloy shell with plate mounted or nm1, dz20 series breaker3. possessing the guarding function against overload and short, etc;4. steel pipe and cable wiring. (v)额定电压ratedvoltage (a)额定电流ratedcurrent (a)防爆标志explosion-proofing marker防护等级protectioncategory防腐等级corrosion-proofing grade进线口螺纹inlet"sthread电缆外径(mm)cable's outside diameter380/100, 125, 160,180, 200,225, 250exde bt4exd bt4ip54w, wf1, wf2g2 27~ 37g21/2 36~ 44g3 56