

# 1000型四川皮带输送机

产品名称	1000型四川皮带输送机
公司名称	成都特瑞矿山机械有限公司
价格	.00/个
规格参数	类型:带式输送机 品牌:特瑞 型号:1000
公司地址	成都市金牛区金府路777号1幢10楼20号
联系电话	13666279887 15828526661

## 产品详情

类型	带式输送机	品牌	特瑞
型号	1000	输送能力	200-320 ( t/h )
功率	5.5 ( KW )	输送距离	50 ( m )
外形尺寸	1000*50 ( m )	重量	2600 ( kg )
适用领域	矿山、水泥		

### 皮带输送机

在工业生产中，皮带输送机可用作生产机械设备之间构成连续生产的纽带，以实现生产环节的连续性和自动化，提高生产率和减轻劳动强度。输送带根据摩擦传动原理而运动，具有输送量大、输送距离长、输送平稳，物料与输送带没有相对运动，噪音较小，结构简单、维修方便、能量消耗少、部件标准化等优点，因而广泛应用于采矿、冶金、化工、铸造、建材等行业的输送和生产流水线以及水电站建设工地和港口等生产部门，用来输送松散物料或成件物品，根据输送工艺要求，可以单台输送，也可多台胶带输送机组成或与其他输送设备组成水平或倾斜的输送系统，以满足不同布置形式的作业线需要。胶带输送机可在环境温度 - 20 至 + 40 范围内使用，输送物料的温度在50 以下.皮带输送机主要由机架、输送皮带、皮带辊筒、张紧装置、传动装置等组成。机身采用优质钢板连接而成，由前后支腿的高低差形成机架，平面呈一定角度倾斜。机架上装有皮带辊筒、托辊等，用于带动和支承输送皮带。有减速电机驱动和电动滚筒驱动两种方式。

皮带输送机技术参数：

胶带宽度(m m)	输送长度 ( m )						输送速度(m/s)	输送量 (t/h)
	功率(kw)							
400	12/2.2	12	20/2.2	4	20	25/3.5 7.5	1.25 2.0	30 60
500	12/3	12	20/3	5.5	30	30/5.5 7.5	1.25 2.0	40 80
650	12/4	12	20/4	5.5	20	30/5.5 11	1.25 2.0	80 120

800	6/4	10 15/4 5.5	15 30/5.5 15	1.25 2.0	120 200
1000	10/5.5	10 20/5.5 11	20 40/11 22	1.25 2.0	200 320
1200	10/7.5	10 20/7.5 15	20 40/15 30	1.25 2.0	320 480

belt conveyer:the belt conveyor produced by our company has the strongpoints of large conveying amount, simple structure, easy maintainance, high standardization degree,etc, which is widely used in mining, metallurgy, coal and other industries. the belt conveyor can be used to transfer bulk materials or materials in pieces.according to different transferring requirements, the transferring system can be of only one belt conveyor or consists of several conveyors, or combined with other transferring equipments. the belt conveyor can be installed horizontally or aslope to meet the needs of different transferring requirements.working principle:the motor drives the driving rollers of the belt conveyor, and drives the roller by the strong belt advances. materials are conveyed from the original place to the place where they are needed.technical parameter:

belt width(mm)	belt length (m) / power (kw)			belt speed (m/s)	capacity (t/h)
500	12/3	12-20/4-5.5	20-30/5.5-7.5	1.3-1.6	45-100
650	12/4	12-20/5.5	20-30/7.5-11	1.3-1.6	70-120
800	10/4	10-15/5.5	15-30/7.5-15	1.3-1.6	120-180
1000	10/5.5	10-20/7.5-11	20-40/11-22	1.3-2.0	160-250
1200	10/7.5	10-20/11	20-40/15-30	1.3-2.0	200-400