

Glas-Col DIGITROL II 数显温控104A PL624

产品名称	Glas-Col DIGITROL II 数显温控104A PL624
公司名称	长沙巴溪仪器有限公司
价格	9800.00/台
规格参数	PL524:100 PL624:100 PL924:100
公司地址	长沙市芙蓉区远大一路408号中栋406房
联系电话	0731-89820291 18974821365

产品详情

DIGITROL II

The DigiTrol II uses a microprocessor-based, user-selectable control mode temperature control. The control features a digital dual output display for set point and process temperature indication. The automatic-tuning feature ensures increased temperature accuracy with minimum overshoot. Easy set-up and simple input commands make this control very “ user friendly. ” The load and the thermocouple receptacles are located on the front panel for easy accessibility. Features automatic cold junction compensation and thermocouple break protection.

Furnished with an immersion thermocouple with 6"-long stainless steel probe.

Specifications

Electrical: Lighted on/off power switch with auxiliary LED indication, fuse protection,

3-wire load receptacle, and 3-wire line cord with molded plug.

Control Type: PID parameters with auto/manual mode option.

Accuracy: 0.1% of span.

Display: Dual, 4-digit LED.

Set Point: Up/down keys. ° F or ° C display,

user selectable.

104A PL612 15A@120V, 1,800W 0-750 ° C Type J 3.0

104A PL612K 15A@120V, 1,800W -200-1250 ° C Type K 3.0

104A PL612T 15A@120V, 1,800W -200-350 ° C Type T 3.0

104A PL624 10A@240V, 2,400W 0-750 ° C Type J 3.0

104A PL624K 10A@240V, 2,400W -200-1250 ° C Type K 3.0

104A PL624T 10A@240V, 2,400W -200-350 ° C Type T 3.0