

包装性能检测 木箱

产品名称	包装性能检测 木箱
公司名称	鉴联合国检（广州）检测技术有限公司
价格	1000.00/个
规格参数	报告用途:质量评价 样品量:150g 检测周期:5个工作日
公司地址	广州市天河区岑村沙埔大街323号B-5栋
联系电话	15915704209 13620111183

产品详情

包装：运输包装及称、外包装、集合、内包装、保护产品数量、品质和便于运输、储存而进行的外层物数(层)量、并促进包装标准、降低包装费用、减轻装卸搬运劳动强度、便利运输、保证货

一、运输包装检测：

危险货物包装检测常用标准有：

联合国《关于危险货物运输的建议书规章范本》(TDG);《国际海运危险货物规则》(IMDG);

《空运危险货物安全运输技术规则》(ICAO);《危险品规则》(IATA);

国家水运、空运、铁路运输、公路运输等安全规范及危险货物包装标准: SN/T0370,JT/T617等行业标准。

液压试验 气密试验

堆码试验 跌落试验

该检测可对危险品包装的桶类、罐类、箱类、袋类、复合包装等形式的包装，按SN、GB、国际海运危规、国际空运危规及公路、铁路运输要求进行各类试验，还可对柔性集装箱散包装进行全项性能测试。广州海关技术中心实验室能够承担全部法定检测项目，具备打火机、点火qiang常规检验、小压力容器及气雾罐、喷雾罐常规检测能力，所出报告全国通用。

二、可代办申报包装性能检测，广州海关技术中心出具相关检测报告。

具体检测内容可参考：类别 危险品包装(运输包装、打火机、气压罐)

产品名称 纸箱、木箱、纸板桶、塑料桶/罐、金属桶/罐、打火机、气雾罐、中型散货箱

检测标准 联合国《关于危险货物运输的建议书规章范本》(第17修订版

ST/SG/AC.10/1/Rey.17

ICAO危险物品安全航空运输《技术细则》2011-2012年版 Dangerous Goods Regulations 2013 5th

国际海运危险货物规则2012修订版

GB19269-2009 铁路运输危险货物包装检验安全规范 GB19270-2009 水路运输危险货物包装检验安全规范

GB19433-2009 空运危险货物包装检验安全规范

SN/T03701 出口危险货物包装检验规程第1部分:总则

SN/T03703 出口危险货物包装检验规程第3部分:使用鉴定 GB19160-2008 包装容器危险品包装用塑料罐

SN/T03692-2009 海运出口危险货物钢桶集装袋性能检验规程

SN/T0324-1994 海运出口危险货物小型气体容器包装检验规程 GB13042-2008 包装容器铁质气雾罐

SN/T07611-2011 出口危险品打火机检验规程 ISO9994:2005 打火机安全规范

吴技策中心箱深圳海关技术中心是从事进出口危险货物、石油、化肥、电子电器、高与广州海

especially during the crucial late spring and summer months. Shifting those rains—or losing even a small percentage—could have ripple effects on agriculture in the Plains states, which are a main food source for the country.