

ADEL变频器DFX6012

| | |
|------|--------------------------|
| 产品名称 | ADEL变频器DFX6012 |
| 公司名称 | 上海航欧机电设备有限公司 |
| 价格 | .00/个 |
| 规格参数 | |
| 公司地址 | 上海市普陀区中江路388弄1号楼905室 |
| 联系电话 | 021-51085161 13045641319 |

产品详情

2017年ADELsystem工厂上海航欧中国区销售

ADEL电源ADEL开关电源ADEL变频器ADEL差压变频器ADELSYSTEM开关电源、ADELSYSTEMADELSYS
TEM电源供应器、ADELSYSTEM模块、ADELSYSTEM接口

2017年 ADELsystem工厂上海航欧中国区销售

意大利ADELSYSTEM开关电源SCE12ADELSYSTEM电源、ADELSYSTEM开关电源、ADELSYSTEM、AD
ELSYSTEM电源供应器、ADELSYSTEM模块、ADELSYSTEM接口

上海航欧机电设备有限公司从事进口机电设备、仪器仪表等备品备件的销售，是经营世界各地进口设备
机电配件的企业。上海航欧公司与众多品牌电子元件供应商建立良好的合作关系，在欧美、日本等地
形成了稳定的供应网络，良好的供应商关系和多年的行业经验，使我们在价格及货期上有优势。

ADELSYSTEM开关电源、ADELSYSTEMADELSYSTEM电源供应器、ADELSYSTEM模块、ADELSYSTEM
接口

2017年ADELsystem工厂上海航欧中国区销售

主要型号：

DFLEX

Switchingpowersupplies-Input115 – 230Vac

DFX1512ASwitchingPowersupplyOutput:12Vdc1AInput:115-230VacD/P

DFX4512ASwitchingPowersupplyOutput:12Vdc3AInput:115-230VacD/P

ADEL 变送器 DFX6012ASwitchingPowersupplyOutput:12Vdc6AInput:115-230VacD/P

DFX1524ASwitchingPowersupplyOutput:24Vdc0.5AInput:115-230VacD/P

DFX4524ASwitchingPowersupplyOutput:24Vdc1.75AInput:115-230VacD/P

DFX6024ASwitchingPowersupplyOutput:24Vdc3AInput:115-230VacD/P

FLEX

FLEX6005ASwitchingPowersupplyOutput:5Vdc5AInput:115-230VacD

FLEX6012ASwitchingPowersupplyOutput:12Vdc6AInput:230VacD

FLEX17012ASwitchingPowersupplyOutput:12Vdc14AInput:230VacD

FLEX28012ASwitchingPowersupplyOutput:12Vdc20AInput:230VacD

FLEX6024ASwitchingPowersupplyOutput:24Vdc3AInput:115-230VacD

FLEX9024ASwitchingPowersupplyOutput:24Vdc5AInput:115-230VacD

FLEX17024ASwitchingPowersupplyOutput:24Vdc7,5AInput:115-230VacD

FLEX28024ASwitchingPowersupplyOutput:24Vdc14AInput:115-230VacD

FLEX50024ASwitchingPowersupplyOutput:24Vdc25AInput:115-230VacD

Switchingpowersupplies-Input230-400 – 500Vac2and3Phase

FLEX9024BSwitchingPowersupplyOutput:24Vdc5A(2Phase)D

FLEX17024BSwitchingPowersupplyOutput:24Vdc7,5A(2Phase)D

FLEX28024BSwitchingPowersupplyOutput:24Vdc14A(2Phase)D

FLEX50024BSwitchingPowersupplyOutput:24Vdc25A(3Phase)D

FLEX17048ASwitchingPowersupplyOutput:48Vdc3,8AInput:115-230VacD

FLEX28048ASwitchingPowersupplyOutput:48Vdc7,5AInput:115-230VacD

FLEX50048ASwitchingPowersupplyOutput:48Vdc12,5AInput:115-230VacD

PST

Switchingpowersupplies-Input400 – 480Vac3-Phase

PST2440BSwitchingPowersupplyOutput:24Vdc40AD

"PSTseries"Switchingpowersupplies-Input400 – 480Vac3-Phase(DriverApplications)

PST4810BSwitchingPowersupplyOutput:48Vdc10A-35Amax.D

SW

AC/DCandDC/DCConverters"NotIsolated"-LowVoltageInputACorDC24V

Input:24V

SW053LC Switching Powersupply Output:5Vdc3AD

SW103LC Switching Powersupply Output:10Vdc3AD

SW125HP Switching Powersupply Output:12Vdc5AD

SW243LC Switching Powersupply Output:24Vdc3AD

SW245HP Switching Powersupply Output:24Vdc5AD

SW247HP Switching Powersupply Output:24Vdc7AD

Input:48V

SW245HP/48 Switching Powersupply Output:24Vdc3A-Input48VdcD

PFAL

AC/DcandDC/DCC Converters" Not Isolated"-Low Voltage Input AcorDC-Adjustable output Vdc +/-10%

PFAL2410 Switching Powersupply Output:24Vdc10AD

PFAL2420 Switching Power supply Output:24Vdc 20A D

Input: 48V

PFAL2420/48 Switching Power supply Output:24Vdc 15A - Input 48Vdc D

Input 6-28Vac/8-39Vdc

PFALVP3 Vout Adjustable from 1.25 - 27 Vdc 2 A D

SCM

Switching power supplies - Input 115 – 230 Vac

SCM4012A Switching Power supply Output: 12Vdc 3.5 A Input: 115 - 230 Vac

P

SCM7512A Switching Power supply Output: 12Vdc 6.3 A Input: 115 - 230 Vac

P

SCM10012A Switching Power supply Output: 12Vdc 8.5 A Input: 115 - 230 Vac P

SCM4024A Switching Power supply Output: 24Vdc 1.8 A Input: 115 - 230 Vac

P

SCM7524A Switching Power supply Output: 24Vdc 3.2 A Input: 115 - 230 Vac

P

SCM10024A Switching Power supply Output: 24Vdc 4.5 A Input: 115 - 230 Vac P

Product group 2 DC / DC Converter

SUP

STEP-UP DC/DC Converters "Not Isolated"- Low Input Vdc- Adjustable output Vdc
+/-10%

Input: 12V

SUP3-1224 STEP-UP Dc/Dc ing. 12V out. 24V 3A D

SUP6-1224 STEP-UP Dc/Dc ing. 12V out. 24V 6A D

SUP3-1230 STEP-UP Dc/Dc ing. 12V out. 30V 3A D

SUP3-1240 STEP-UP Dc/Dc ing. 12V out. 40V 3A D

Input: 24V

SUP3-2448 STEP-UP Dc/Dc ing. 24V out. 48V 3A D

SUP6-2448 STEP-UP Dc/Dc ing. 24V out. 48V 6A D

SUP3-2460 STEP-UP Dc/Dc ing. 24V out. 60V 2,5A D

SUP6-2460 STEP-UP Dc/Dc ing. 24V out. 60V 6A D

SUP ISO

DC/DC Converters "Isolated"- Low Voltage Input DC to DC - Adjustable output Vdc
+/-10%

Input 12Vdc

SUP30-12/24 Switching Power supply Input 10 - 18 Vdc Output: 24 Vdc 1.3 A P

SUP50-12/12 Dc/Dc Converter Input 10 - 15 Vdc Output: 12 Vdc 4.2 A (Isolated) P

SUP50-12/24 Switching Power supply Input 10 - 18 Vdc Output: 24 Vdc 2.1 A P

Input 24Vdc

SUP30-24/24 Switching Power supply Input 18 - 36 Vdc Output: 24 Vdc 1.3 A P

SUP50-24/24 Switching Power supply Input 10 - 18 Vdc Output: 24 Vdc 2.1 A P

SUP70-24/24 Switching Power supply Input 18 - 36 Vdc Output: 24 Vdc 3 A P

SUP100-24/24 Switching Power supply Input 18 - 36 Vdc Output: 24 Vdc 4.2 A P

SUP200-24/24 Switching Power supply Input 18 - 36 Vdc Output: 24 Vdc 8.4 A P

Input 48Vdc

SUP30-48/24 Switching Power supply Input 36 - 72 Vdc Output: 24 Vdc 1.3 A P

SUP70-48/24 Switching Power supply Input 36- 72 Vdc Output: 24 Vdc 3 A P

SUP150-48/24 Switching Power supply Input 36 - 72 Vdc Output: 24 Vdc 6.3 A P

SUP200-48/24 Switching Power supply Input 36 - 72 Vdc Output: 24 Vdc 8.4 A P

SUP200-48/12 Switching Power supply Input 36 - 72 Vdc Output: 12 Vdc 16.7 A P

DINSUP Support for Din Rail "SUP Line" D

Product group 3 DC-UPS

CBI

DC-UPS - ALL IN ONE = Battery Charger + Continuity BackUp Module + Power Supply in one unit

Input 115-230-270

Vac

CBI123A DC-UPS Out 12 Vdc 3A In 115-230-270 Vac, no NiCd battery, with Temperature Compensation D

CBI123A-NiCd DC-UPS Out 12 Vdc 3A In 115-230-270 Vac, NiCd battery enabled, no Temperature Compensation D

CBI126A DC-UPS Out 12 Vdc 6A In 115-230-270 Vac, no NiCd battery, with Temperature Compensation D

CBI126A-NiCd DC-UPS Out 12 Vdc 6A In 115-230-270 Vac, NiCd battery enabled, no Temperature Compensation D

CBI1210A DC-UPS Out 12 Vdc 10A In 115-230-270 Vac, no NiCd battery, with Temperature Compensation D

CBI1210A-NiCd DC-UPS Out 12 Vdc 10A In 115-230-270 Vac, NiCd battery enabled, no Temperature Compensation D

CBI1235A DC-UPS Out 12 Vdc 35A In 115-230-270 Vac - MODbus connection D

CBI1235AP DC-UPS Out 12 Vdc 35A In 115-230-270 Vac (parallel connection enabled) D

CBI1235AR DC-UPS Out 12 Vdc 35A In 115-230-270 Vac - (Battery charging redundancy, MR220 module required) D

Input 115 – 230-270
Vac

CBI243A DC-UPS Out 24 Vdc 3A In 115-230-270 Vac, no NiCd battery, with Temperature Compensation D

CBI243A-NiCd DC-UPS Out 24 Vdc 3A In 115-230-270 Vac, NiCd battery enabled, no Temperature Compensation D

CBI245A DC-UPS Out 24 Vdc 5A In 115-230-270 Vac, no NiCd battery, with Temperature Compensation D

CBI245ATB DC-UPS Out 24 Vdc 5A In 115-230-270 Vac, no NiCd battery, with Temperature Compensation, Time Buffering 5' D

CBI245ATB1 DC-UPS Out 24 Vdc 5A In 115-230-270 Vac, no NiCd battery, with Temp. Compensation, Time Buffering 0.5 min in Low batt; UPS Enabling D

CBI245A-NiCd DC-UPS Out 24 Vdc 5A In 115-230-270 Vac, NiCd battery enabled, no Temperature Compensation D

CBI2410A DC-UPS Out 24 Vdc 10A In 115-230-270 Vac-No Battery start-up, No NiCd battery, Yes Temperature compensation D

CBI2410ATB DC-UPS Out 24 Vdc 10A In 115-230-270 Vac-No Battery start-up, No NiCd battery, Yes Temperature compensation, Time Buffering 5' D

CBI2410A-NiCd DC-UPS Out 24 Vdc 10A In 115-230-270 Vac-No Battery start-up, Yes NiCd battery, No Temperature compensation D

CBI2410A/S DC-UPS Out 24 Vdc 10A In 115-230-270 Vac-Yes Battery start-up, No NiCd battery, Yes Temperature compensation D

CBI2420A DC-UPS Out 24 Vdc 20A In 115-230-270 Vac - MODbus connection D

CBI2420AP DC-UPS Out 24 Vdc 20A In 115-230-270 Vac (parallel connection enabled) D

CBI2420AR DC-UPS Out 24 Vdc 20A In 115-230-270 Vac - (Battery charging redundancy, MR220 module required) D

CBI485A DC-UPS Out 48 Vdc 5A In 115-230-270 Vac-No Battery start-up,No NiCd battery,Yes Temperature compensation D

CBI485A-NiCd DC-UPS Out 48 Vdc 5A In 115-230-270 Vac-No Battery start-up, Yes NiCd battery,NoTemperature compensation D

CBI485A/S DC-UPS Out 48 Vdc 5A In 115-230-270 Vac -Yes Battery start-up,No NiCD battery,Yes Temperature compensation D

CBI4810A DC-UPS Out 48 Vdc 10A In 115-230-270 Vac - MODbus connection D

CBI4810AP DC-UPS Out 48 Vdc 10A In 115-230-270 Vac (parallel connection enabled) D

CBI4810AR DC-UPS Out 48 Vdc 10A In 115-230-270 Vac - (Battery charging redundancy, MR220 module required) D

Input 115 – 230-270
Vac

CBI2801224A DC UPS Out 12-24 Vdc(selectable)280W In:115-230-277Vac Modbus D

Input 230 - 400 - 500
Vac

CBI2801224B DC UPS Out 12-24 Vdc(selectable)280W In:230-400-500Vac Modbus D

Accessories for CBI

RTCONN Connector for position 5 (Start from battery) with Two Wires (2 m)

RJTEMP451 Temperature compensation probe with connector 1m (For all CBI models except for CBI280)

RJTEMP453 Temperature compensation probe with connector 3m (For all CBI models except for CBI280)

RJTEMP111 Temperature compensation probe with RJ11 connector 1m (Specific for CBI2801224A and B)

RJTEMP113 Temperature compensation probe with RJ11 connector 3m (Specific for CBI2801224A and B)

ERJ.CBI.004 Paralleling Cable Connector RJ45/RJ45 1m (Suitable for CBI1235A,2420A,4810A and for Modbus connection on CBI280)

Demo Kit

CBI demo Kit Demonstrative panel composed of CBI1210A and Batt1.2 for Show room

Input 400 Vac

UPS2410B DC-UPS, 400Vac in, 10A 24 Vdc out D

UPS2410B/RS DC-UPS, 400Vac in, 10A 24 Vdc out - RS232 D

PSM

Switching power supplies and Battery Charger - Input 115 – 230 Vac

PSM123A Out Load 13.8 V 3A; Battery 13.3; 0.1A D

PSM241A Out Load 24 V 1.5 A; Battery 27 V ; 0.1A D

UPL

Switching power supplies and Battery Charger - Input 115 – 230 Vac

UPL5512A Out Load 13.8 V 4 A; Battery 13.4 ; 0.23A D

UPL10012A Out Load 13.8 V 6A; Battery 13.3; 0.5A D

UPL5524A Out Load 27.6 V; 2A; Battery 26.5; 0.16A D

UPL10024A Out Load 27.6 V 3A; 27.V; 0.5A D

Product group 4 Battery Charger

CB

CB - Battery chargers. They Test and Recharge the battery Input 115 – 230-270 Vac

CB123A Battery Charger 3 Level Out 12 Vdc 3A In 115-230-270 Vac D

CB123A/48 Battery Charger 3 Level Out 12 Vdc 3A In 48 Vdc D

CB1210A Battery Charger 3 Level Out 12 Vdc 10A In 115-230-270 Vac D

CB1235A Battery Charger 3 Level Out 12 Vdc 35A In 115-230-270 Vac D

CB243A Battery Charger 3 Level Out 24 Vdc 3A In 115-230-270 Vac D

CB245A Battery Charger 3 Level Out 24 Vdc 5A In 115-230-270 Vac D

CB2410AC Battery Charger 3 Level Out 24 Vdc 10A In 115-230-270 Vac D

CB2420A Battery Charger 3 Level Out 24 Vdc 20A In 115-230-270 Vac D

CB363A Battery Charger 3 Level Out 36 Vdc 3A In 115-230-270 Vac D

CB12245A Battery Charger 4 Level Out 12-24 Vdc(selectable)120W
In:115-230-277Vac D

Product group 5 Battery Bank

VRLA

Enclosure + Battery

BATT 123 12 Vdc Battery 3.2Ah (N.1 battery+Battery Chest) P

BATT 123DIN 12 Vdc Battery 3.2Ah (N.1 battery+Battery Chest) with DIN clip D

BATT 127 12 Vdc Battery 7.2Ah (N.1 battery+Battery Chest) P

BATT 127DIN 12 Vdc Battery 7.2Ah (N.1 battery+Battery Chest) with DIN clip D

BATT 1.2Ah 24 Vdc Battery 1.2Ah (N.2 batteries+Battery Chest) P

BATT 1.2AhDIN 24 Vdc Battery 1.2Ah (N.2 batteries+Battery Chest) with DIN
clip D

BATT 3.2Ah 24 Vdc Battery 3.2Ah (N.2 batteries+Battery Chest) P

BATT 3.2AhDIN 24 Vdc Battery 3.2Ah (N.2 batteries+Battery Chest) with DIN
clip D

BATT 7.2Ah 24 Vdc Battery 7.2Ah (N.2 batteries+Battery Chest) P

BATT 7.2AhDIN 24 Vdc Battery 7.2Ah (N.2 batteries+Battery Chest) with DIN
clip D

Enclosure

BATTHOLDER123 Battery chest for battery 12V/3.2Ah - without battery P

BATTHOLDER123DIN Battery chest for battery 12V/3.2Ah - without battery with DIN
clip D

BATTHOLDER127 Battery chest for battery 12V/7.2Ah - without battery P

BATTHOLDER127DIN Battery chest for battery 12V/7.2Ah - without battery with DIN clip D

BATTHOLDER1212 Battery chest for battery 12V/12Ah - without battery P

Small VRLA

BAT1.2VRLA 24 Vdc Battery 1.2Ah (N.2 batteries+Battery Enclosure) DIN & Wall mount D/P

BAT3.4VRLA 24 Vdc Battery 3.2Ah (N.2 batteries+Battery Enclosure) DIN & Wall mount D/P

BAT7.2VRLA 24 Vdc Battery 7.2Ah (N.2 batteries+Battery Enclosure) DIN & Wall mount D/P

BAT12VRLA 24 Vdc Battery 12Ah (N.2 batteries+Battery Enclosure) Wall mount P

Enclosure

BTH1.2VRLA 24 Vdc Battery Enclosure for N.2 batteries 12V/1.2Ah - without battery, DIN & Wall mount D/P

BTH3.4VRLA 24 Vdc Battery Enclosure for N.2 batteries 12V/3.4Ah - without battery, DIN & Wall mount D/P

BTH7.2VRLA 24 Vdc Battery Enclosure for N.2 batteries 12V/7.2Ah - without battery, DIN & Wall mount D/P

BTH12VRLA 24 Vdc Battery Enclosure for N.2 batteries 12V/12Ah - without battery, Wall mount P

SFP

SFP544 Panel for EN54.4 field. Can contain batteries VRLA from 1.2 up to 18Ah and all range of DC UPS "CBI" P

Product group 6 Interfaces

MR

Decoupler

MR220 Decoupling Module In - Out 10 - 60 Vdc 25A D

Product group 7 Multimediality

Power Bus

PBI122 2017年ADELsystem工厂上海航欧中国区销售

