

LEH7系列缩小体插件高频低阻抗电容-(小型化高频率低E.S.R品)

产品名称	LEH7系列缩小体插件高频低阻抗电容-(小型化高频率低E.S.R品)
公司名称	华凯电容(深圳)有限公司
价格	.00/个
规格参数	封装:圆柱形 型号:100uf25v 5x7 温度:105 ° c
公司地址	深圳市龙岗区平湖街道新木社区新木路254号B栋一楼
联系电话	0755-84006779 15817353058

产品详情

LEH7 series系列高频低阻抗电容- (小型化高频率低E.S.R品)

铝电解电容100UF25V 5*6.5 缩小体插件电解电容

LEH560uf10v 8x9.220uf16v 6.3x7

LEH7系列缩小体插件高频低阻抗电容-(小型化高频率低E.S.R品)

1.高频率低ESR，寿命2000小时，1050C 2.适用于电脑主机板，高保真音箱，高分辨数电等电子线路中
Specifications 1 使用温度范围 Operating Temperature Range-40 to + 1050C 2 定格电压范围 Rated Working Voltage Range 3 静电容量范围 Capacitance Tolerance 0.47-4700F 4 静电容量容许差 Capacitance Tolerance $\pm 20\%$ (at + 25 0C , 120Hz) 5 泄漏电流 Leakage Current I 0.01CV or 2 (A) after three minutes Application of rated working voltage + 25 6 损失角 Dissipation Factor (tan) (120Hz/ + 25) Working Voltage 6.3 10 16 25 35 50 63 100 tan max.0.18 0.12 0.10 0.08 0.07 0.06 0.05 0.05 7 温度特性 (at 120 Hz) Characteristics at low temperature (stability at 120Hz) Working Voltage (V) 6.3 10 16 25 35 50 63 63 100 -25 / + 25 4 3 2 2 2 2 2 2 -40 / + 25 8 4 3 3 3 3 3 4 4 8 高温负荷特性 High Temperature Loading After of DC rated working voltage at + 105 , The capacitor shall meet the following limits : Post test requirements at + 25 Leakage current the Initial specified value Capacitance change $\pm 20\%$ of initial measured value Dissipation Factor (tan) 200% of initial specified value 9 高温无负荷特性 Shelf Life After storage for + 105 with no voltage applied. Post test requirements at + 25 Same limits for high temperature lading.