

# 雪佛龙Taro 40 XL 40船用柴油机油Chevron Taro 30 DP 40

产品名称	雪佛龙Taro 40 XL 40船用柴油机油Chevron Taro 30 DP 40
公司名称	深圳市润富源科技有限公司
价格	4000.00/桶
规格参数	
公司地址	深圳市龙华区龙华街道狮头岭新村西区14栋302
联系电话	13728920503

## 产品详情

### 雪佛龙Taro 40 XL 40船用柴油机油Chevron Taro 30 DP 40

Chevron offers the marine industry a complete range of high-performance marine lubricants. Product development is performed at Chevron laboratories, and all marine engine oils complete exhaustive field trials before introduction. Chevron products are manufactured to consistently high standards at more than fifty blending plants worldwide. Supply is available at more than 400 ports. The following table gives a brief description and typical physical properties of each product. For more details, please refer to individual product information at [www.chevron.com/marineproducts](http://www.chevron.com/marineproducts) (under Lubricants > Product Information), or contact your local Chevron representative or marketing office.

#### Slow-speed Engine Oils

Taro Special HT 70 50 0.93 247 20.0 105 270 – 15 70 Slow-speed diesel engine cylinder oil for high load application.

Taro Special 70\* 50 0.93 213 19.0 100 270 – 15 70 Slow-speed diesel engine cylinder oil.

Taro Special HT LS 40 50 0.92 247 21.0 100 270 – 15 40 Slow-speed diesel engine cylinder oil for low sulphur application.

Veritas 800 Marine 20 20 0.88 68 8.5 95 240 – 12 5.4 Slow-speed engine system oil for viscosity adjustment.

Veritas 800 Marine 30 30 0.89 111 12.0 95 240 – 12 5.4 Slow-speed engine system oil.

#### Medium-speed Engine Oils

Delo 1000 Marine 30 30 0.89 94 12.0 100 240 – 18 12 Medium-speed engine oil. API CF. Fuel S level up to 1.5%.

Delo 1000 Marine 40 40 0.90 135 14.0 100 240 – 18 12 Medium-speed engine oil. API CF. Fuel S level up to 1.5%.

Taro 20 DP 30 30 0.90 95 11.0 100 240 – 12 20 Medium-speed engine oil. API CF. Fuel S level up to 2%.

Taro 20 DP 40 40 0.90 135 14.0 100 240 – 12 20 Medium-speed engine oil. API CF. Fuel S level up to 2%.

Taro 30 DP 30 30 0.90 95 11.0 100 240 – 12 30 Medium-speed engine oil. API CF. Fuel S level up to 4%.

Taro 30 DP 40 40 0.90 135 14.0 100 240 – 12 30 Medium-speed engine oil. API CF. Fuel S level up to 4%.

Taro 40 XL 40 40 0.91 135 14.0 100 240 – 12 40 Medium-speed engine oil. API CF. Fuel S level up to 4.5%.

Taro 50 XL 40 40 0.92 135 14.0 100 240 – 12 50 Medium-speed engine oil. API CF. Fuel S level up to 4.5%.

For engines with low oil consumption.

### High-speed Engine Oils

Delo 6170 CFO 40 0.91 137 14.0 99 250 – 18 17 Zinc-free engine oil. Generation 4LL and 5. API CF/CF-2.

Delo SHP 30 30 0.89 94 11.0 102 240 – 18 12 Diesel engine oil. API CF/SF. MB 228.2, MTU Type II.

Delo SHP 40 40 0.89 135 14.0 100 240 – 15 12 Diesel engine oil. API CF/SF. MB 228.2, MTU Type II.

Ursa Extra Duty 40 40 0.89 132 14.0 103 240 – 15 7.3 Low ash, two-stroke diesel engine oil. API CF/CF-2. Detroit Diesel.

Ursa Marine 30 30 0.89 92 11.0 104 230 – 27 9.0 High-speed diesel engine oil. API CD/CF, MAN 270, MB 228.0, MTU Type I.

Ursa Marine 40 40 0.89 131 14.0 104 240 – 24 9.0 High-speed diesel engine oil. API CD/CF, MAN 270, MB 228.0, MTU Type I.

Ursa Marine 15W-40 15W-40 0.89 102 14.0 139 225 – 27 9.0 High-speed diesel engine oil. API CG-4, MAN 271, MB 228.1, Volvo VDS.