

抗干扰高灵敏度全自动连续式检针机

产品名称	抗干扰高灵敏度全自动连续式检针机
公司名称	青岛路博建业环保科技有限公司
价格	50000.00/件
规格参数	检测方式:磁场诱导, 数字电路处理 检测灵敏度: Fe 0.8 mm 检测高度:120mm
公司地址	山东青岛城阳区金岭工业园锦宏西路与路博大道 交汇处路博路1号
联系电话	0532-58759055 15315009483

产品详情

适用范围：

服装、婴儿制品、拉链等服装手袋辅料、鞋子、袜子、布料、无纺布巾、地毯、手套、玩具、工艺品等需要检测铁磁性金属杂质检出的行业。

Applicable:

Clothing, baby products, knit goods, underwear, hardware buttons, zippers, socks, non-woven fabrics, embroideries, kimono, beddings, towels, carpets, gloves, toys and handicrafts, etc.

产品特点：

采用日本进口机芯、荷兰输送带、32位数字电脑芯片、新型检测线圈技术。

节电保护，10分钟无被检物通过自动停机、具有防雷防漏电防护措施

触摸式操作面板、探测头八点部位显示确切的断针位置功能

具有声音、灯光和感应强度显示同步功能

所有功能设定在开启总电源后，不启动电机前完成

具有计数功能，区别通过、不良品、总数

具有B/C（辅料/成品）模式切换功能，适应不同产品的检针

超强抗干扰进口红外扫描装置（对吊扇，手机，螺丝刀等铁器移动不误报警）

流水线型外表，ABS外壳，碳钢结构，烘漆工艺，确保机器的检测稳定，性能良好，使用寿命更长

Features:

Mechanism exported from Japan, conveyor belt exported from Holland, non-toxic, new coil technology, computer chip integration adopt digital circuit.

Specially has the protection circuit, it will auto-stop if no detection goods in 10 minutes, Ad Hoc lightning protection circuit leak.

All the function keys are touching-type keys,8 locations can display the accurate position of broken needle

3 ways to alarm: sound, light, and frequency

Open all of the features set the total power; the motor does not start before the completion of.

Can calculate the qualified and unqualified and unqualified amount

Have B/C (accessories/ products) mode switching function, adapt to different products, needle inspection operation.

Strong anti-disturbance (no wrong alarm to the ceiling fan, mobile phones, screwdrivers, etc)

Pipelined appearance, ABS shell, steel structure, first-class baking process, to ensure the detection of the machine stability ,good performance, long service life.

技术参数：

型号	MODEL	SA-630K		
检测方式	Detection method	磁场诱导，数字电路处理 Magnetic field induction, digital circuit		
检测灵敏度	Detection ability	Fe 0.8 mm	Fe 1.0 mm	Fe 1.2 mm
检测高度	Detection Height	120mm	150mm	200mm
检测宽度	Detection width	600mm或客户订制 Net width 600mm-non-standard sizes(custom)		
感应调节	Detection adjustment	0-100级触摸按键调节 Touch buttons adjust the level 0-100		
报警方式	Alarm method	声光报警停机后退并自启动 Sound/light alarm and return, then restart		
电源	Power supply	Ac220V 50-60Hz		
功率	Pated output	100W		
设备尺寸	Dunension	L1650mm × W1050mm × H900mm		
净重	Weight	200KG		