

FWDM

产品名称	FWDM
公司名称	珠海飞宇光电科技有限公司
价格	面议
规格参数	
公司地址	珠海市香洲人民东路81号二层东9号
联系电话	0755-85250091-2816 13926501293

产品详情

Performance Specifications

Parameter	FWDM 4/35	FWDM 5/34	FWDM
Pass Band Wavelength Range (nm)	1480~1500	1540~1560	1260~1480
Reflection Band 1 Wavelength Range (nm)	1260~1360	1260~1360	1540~
Reflection Band 2 Wavelength Range (nm)	1540~1560	1480~1500	
Insertion loss (dB)	Reflect Channel	0.6	
	Pass Channel	0.8	
Pass Band Rippler (dB)	<0.3		
Isolation	Reflect Channel	>15	
	Pass Channel	>30	

Insertion Loss Temperature Sensitivity (dB/)	<0.005
Polarization Dependent Loss (dB)	<0.1
Polarization Mode Dispersion (ps)	<0.1
Directivity (dB)	>50
Return loss (dB)	>50
Maximum Power Handling (mW)	1000
Operating Temperature ()	-20~+80
Storage Temperature ()	-40~+85
Package Dimension (mm)	5.5x34 (L38 for 900um Loose tube)

Specifications may change without notice.

Above specification are for device without connector.

Ordering Information

MWDM	X	X	X	XX
	Wavelength	Fiber Type	Fiber Length	In/Out Connector
	4/35=1490 pass	1=Bare fiber	1=1m	0=None
	/1310&1550 reflect	2=900um loose tube	2=2m	1=FC/APC
	5/34=1550 pass			2=FC/PC
	/1310&1490 reflect			3=SC/APC
	34/5=1310&1490 pass /1550 reflect			4=SC/PC
				5=ST
				6=LC
				S=Specify