

大功率太阳能充电控制器

产品名称	大功率太阳能充电控制器
公司名称	合肥博旭电子科技有限公司
价格	.00/个
规格参数	名称:大功率太阳能充电控制器 产品用途:太阳能发电站和家用系统
公司地址	安徽省合肥市当涂路花溪新村27幢603室
联系电话	0551-63358542 13905697819

产品详情

名称 大功率太阳能充电控制器 产品用途 太阳能发电站和家用系统

适用于各种电池

自动控制输入/输出电压

宽频智能充电

温度感应自动补偿

超负载自动恢复

液晶显示系统精准电压电流等动态参数

过充保护

短路保护

防雷击保护，低压保护

防反接保护

可配备rs232/485与主控制机通讯

太阳能发电基站—大功率控制器

48vdc series product tech-data:

型号model	bwc48-50a	bwc48-100a
充电电压	48v-68v	
charge voltage range		
最大电流	100a	150a
loading current max		
额定电流	50a	100a
rated current		
过充电电压	58v	
over-charge vol.		
过放电压	42.8v	
over-discharge vol.		
空载电流	30ma	
free-load loss		
保护功能	过充保护,短路保护,防雷击保护,低压保护,防反接保护,防反充	
protection mode	over-charge protection, deep-discharge protection, reverse connection protection of load, short circuit protection, reverse current protection at night, over-load protection	
重量net weight (kg)	7.0	
尺寸dimension (mm)	410 x 200 x 160	

96vdc series product tech-data:

型号model	bwc96-50a	bwc96-100a	bwc96-150a	bwc96-200a	bwc96-250a
充电电压	96v-500v				
charge voltage range					
最大电流	100a	150a	200a	250a	300a
loading current max					
额定电流	50a	100a	150a	200a	250a
rated current					
过充电电压	115.2v				
over-charge vol.					
过放电压	86.4v				
over-discharge vol.					
空载电流	30ma				
free-load loss					
保护功能	过充保护,短路保护,防雷击保护,低压保护,防反接保护,防反充				

protection mode	over-charge protection, deep-discharge protection, reverse connection protection of load, short circuit protection, open circuit protection, reverse current protection at night, over-load protection
重量net weight (kg)	7.5
尺寸dimension (mm)	410 x 200 x 160

太阳能发电基站—大功率控制器

120vdc series product tech-data:

型号model	bwc120-50a	bwc120-100a	bwc120-125a	bwc120-150a
充电电压	108v-144v			
charge voltage range				
最大电流	100a	150a	175a	200a
loading current max				
额定电流	50a	100a	125a	150a
rated current				
过充电压	144v			
over-charge vol.				
过放电压	108v			
over-discharge vol.				
空载电流	30ma			
free-load loss				
保护功能	过充保护,短路保护,防雷击保护,低压保护,防反接保护,防反充			
protection mode	over-charge protection, deep-discharge protection, reverse connection protection of load, short circuit protection, open circuit protection, reverse current protection at night, over-load protection			
重量net weight (kg)	8.0			
尺寸dimension (mm)	410 x 200 x 160			

240vdc series product tech-data:

型号model	bwc240-50a	bwc240-100a	bwc240-125a	bwc240-150a
充电电压	198v-264v			
charge voltage range				
最大电流	100a	150a	175a	200a
loading current max				
额定电流	50a	100a	125a	150a
rated current				

过充电压	264v
over-charge vol.	
过放电压	198v
over-discharge vol.	
空载电流	30ma
free-load loss	
保护功能	过充保护,短路保护,防雷击保护,低压保护,防反接保护,防反充
protection mode	over-charge protection, deep-discharge protection, reverse connection protection of load, s protection, open circuit protection, reverse current protection at night, over-load protection
重量net weight (kg)	8.5
尺寸dimension (mm)	410 x 200 x 160