

## 闭孔珍珠岩和玻化微珠

产品名称	闭孔珍珠岩和玻化微珠
公司名称	罗山县中一保温建材厂
价格	1600.00/吨
规格参数	品牌:润珠 型号:110 产地:信阳
公司地址	河南省信阳市罗山县楠杆镇楠杆镇田堰村1
联系电话	18637673767 13837658623

## 产品详情

--	--	--	--

			<p>3.吸水率较大，在应用过程中会出现上述膨胀珍珠岩同样的问题，但在各项指标上要优于膨胀珍珠岩。</p> <p>3. High water absorption, will have similar problems as expanded perlite using, but have better performance than expanded perlite.</p>
闭孔珍珠岩	珍珠岩	1. 容重大	1.不规则的外形，在砂浆中易产生阻力，和易性差，搅拌时间较长，其在砂浆中不易分布均匀，容易造成应力集中，引起空鼓、开裂，大大降低了砂浆的力学性能和热工性能，也影响到保温层的使用寿命。
Hole-close perlite	Perlite	(120~180kg/m)	
		2.吸水率较大	1. irregular shape makes it easy to produce resistance, low workability, long mixing time, makes it unevenly distributed in the mortar, which will cause stress concentration, hollowing and cracking, reduce mechanical property and thermal property greatly, also has impact on the insulation layer service life.
		3.颗粒强度较大	2.容量大，导热系数较差，在砂浆中必须增加轻骨料掺加比列，以满足热工性能标准要求，轻骨料掺加量的增加必然会降低砂浆的力学性能或增加胶凝材料成本。
		4.导热系数大	2. High capacity with bad heat conductivity, need to increase light aggregate ratio to meet the thermal property requirement, but adding light aggregate will reduce mortar mechanical property and increase gelled materials cost.
		1. High density	
		2. High water absorption	
		3. High particle strength	
		4. High heat conductivity	