

# FG7OH1M1/FG7OH2M1电缆 适用于高危火灾环境

产品名称	FG7OH1M1/FG7OH2M1电缆 适用于高危火灾环境
公司名称	北京北自南瑞电气设备有限公司
价格	.59/米
规格参数	埃因电线电缆:见详情 FG7OH:见详情 上海:见详情
公司地址	北京市丰台区潘家庙路9号院14号楼一层102
联系电话	13681886808 13681886808

## 产品详情

### FG7OH1M1/FG7OH2M1电缆 适用于高危火灾环境

#### 应用 / APPLICATIONS

这些电缆适用于高危火灾环境，可保证安全和防止系统设备遭腐蚀性气体损害，比如学校、医院，公共场所、宾馆、超市、管道、影院、剧院、舞厅、公共机构等)。适宜固定安装在室内和室外、墙壁和金属框架上。

These cables are suitable for high risk of fire environment, can guarantee the safety and prevention system equipment damage by corrosive gas, such as schools, hospitals, public places, hotels, supermarkets, pipeline, cinemas, theaters, dance halls, public institutions, etc.). Suitable for fixed installed in indoor and outdoor, wall and metal frame.

#### 标准/STANDARDS

CEI 20-11, CEI 20-13, CEI 20-22 III, CEI 20-37, CEI 20-38, IEC 60502-1, IEC60228, IEC60332.1, IEC60332.3-C, IEC60754.1

#### 电缆结构 / CONSTRUCTION FEATURES

导体 软退火铜线，5级。覆盖防火云母带

Conductor Soft annealed copper cord, class 5. Covered with fire proof mica tape

绝缘 HEPR, G7绝缘，遵循CEI 20-11 - CEI 20-3

Insulation With the quality of the G7 HEPR.

芯线颜色 色彩编码遵循DIN VDE 0293-308

色 Cores Colour	Color code follow DIN VDE 0293-308
填充/Screen	非纤维非吸湿性填料 The fiber non hygroscopic filler
屏蔽/shielding	- 铜带屏蔽(FG7OH1M1) Copper tape screened (FG7OH1M1) - 铜丝编织屏蔽(FG7OH2M1) Copper wire braided shielding (FG7OH2M1)
护套/Sheath	低烟无卤热塑性复合物M1外护套 low smoke zero halogen thermoplastic compounds M1 outer sheath
技术特性 / PROPERTIES	
工作电压 Rated Voltage	600/1000 V
测试电压	4000V
抗拉/Tensile	5KG/mm
*小弯曲半径/ Radius	8 x D 电缆直径
工作温度 Working temperature	0 C ~ +90 C
短路时 可达温度 Max. Short circuit +250 C	
阻燃/FR	CEI 20-22 II - IEC 60332-34, CEI 20-35 - IEC 60332-1
绝缘电阻IR	10 M x km

具有认证/CERTIFICATIONS

CE认证 UL认证