

诺赛特高频头，诺赛特抗5G干扰高频头，Norsat5150RF高频头

产品名称	诺赛特高频头，诺赛特抗5G干扰高频头，Norsat 5150RF高频头
公司名称	深圳市南山区鑫空电子商行
价格	1250.00/个
规格参数	品牌:诺赛特 型号:5150RF
公司地址	深圳市南山区沙河街道下白石三坊28号79
联系电话	13302456150 18123872259

产品详情

???Norsat5150RF?5G?????C??????????????

产品型号：Norsat-5150RF

Norsat-5150R, C-Band PLL LNB为广电职业专用锁相环抗5G高频头，在国内各电视台及监测站长时间运用，其安稳性为国际水平，彻底满足广播电视星通讯等信号接纳的需求。

Norsat-5150R, C-Band PLL LNB是目前市场占有率高的能够抑制5G基站信号关于星地球站C波段搅扰的单极化高频头，性能牢靠安稳，增益高

产品技术数据：

KEY SPECIFICATIONS

Product Family

5150R Series

Band

C-Band

LO Type	PLL
# of onboard LOs	Single-band
LO Stability	+/- 150 KHz
Noise Figure	25 K
Input Frequency - Band 1	C-Band: 3.70 - 4.20 GHz
Output Frequency 1	L-Band: 950 - 1450 MHz

RF SPECIFICATIONS

LO Frequency 1	5.15 GHz
Phase Noise @ 1KHz offset	-65 dBc/Hz
Phase Noise @ 10KHz offset	-80 dBc/Hz
Phase Noise @ 100KHz offset	-95 dBc/Hz
Conversion Gain	62 dB typ, 55 dB min, 70 dB max
Input VSWR	2.5 : 1
Output VSWR	2.5 : 1
Output P1dB compression point	5 dBm

ELECTRICAL SPECIFICATIONS

Power Requirements	12 - 24 V
Current Drain	250 mA

INTERFACE SPECIFICATIONS

RF Input Connector	CPR 229G
RF Output Connector	F-75 Ohm

M & C SPECIFICATIONS

LED Indicators	None
----------------	------

ENVIRONMENTAL SPECIFICATIONS

Temperature - Operational	-40 ° C to +60 ° C
---------------------------	--------------------

Humidity

0 - 95%

PHYSICAL SPECIFICATIONS

Dimensions (L x W x H)

190 x 115 x 78 mm

Weight

580 g