

# 日本NOHKEN能研FR20 FR30连杆浮球多点式液位开关

|      |  |
|------|--|
| 产品名称 | 日本NOHKEN能研FR20<br>FR30连杆浮球多点式液位开关        |
| 公司名称 | 山东展悦电子科技有限公司                             |
| 价格   | .00/件                                    |
| 规格参数 | 品牌:日本NOHKEN能研<br>型号:FR20系列<br>型号2:FR30系列 |
| 公司地址 | 山东省济宁市邹城市东城区尚兰路悦邻中心2号<br>楼508室           |
| 联系电话 | 0537-5196811 18954071837                 |

## 产品详情

日本NOHKEN能研FR20 FR30系列连杆浮球液位开关

FR20S-1P日本能研NOHKEN连杆液位开关FR20S-2P

FR20S-1P FR20S-2P FR20S-3P FR20S-4P FR20S-5P FR20S-6P

FR20VS的型号有;材质为PVC

FR20VS-1P FR20VS-2P FR20VS-3P FR20VS-4P FR20VS-5P FR20VS-6P

FR20PS的型号有:材质为:PP

FR20PS-1P FR20PS-2P FR20PS-3P FR20PS-4P FR20PS-5P

FR30HVS的型号有:材质为:CPVC

FR20HVS-1P FR20HVS-2P FR20HVS-3P FR20HVS-4P FR20HVS-5P

FR20S6:为316不锈钢. FR20S6L为316L不锈钢

FR20S具体型号有:材质为304

FR20S-1P FR20S-2P FR20S-3P FR20S-4P FR20S-5P FR20S-6P

FR20VS的型号有;材质为PVC

FR20VS-1P FR20VS-2P FR20VS-3P FR20VS-4P FR20VS-5P FR20VS-6P

FR20PS的型号有;材质为:PP

FR20PS-1P FR20PS-2P FR20PS-3P FR20PS-4P FR20PS-5P

FR30HVS的型号有;材质为:CPVC

FR20HVS-1P FR20HVS-2P FR20HVS-3P FR20HVS-4P FR20HVS-5P

FR20S6:为316不锈钢. FR20S6L为316L不锈钢

NOHKEN日本能研FR20系列连杆液位开关FR20S-1PFR20S-2PFR20S-3PFR20S-4P

FR20S-1P日本NOHKEN日本能研连杆液位开关FR20S-2P

FR20S-1PFR20S-2PFR20S-3PFR20S-4PFR20S-5PFR20S-6P

FR20VS的型号有;材质为PVC

FR20VS-1PFR20VS-2PFR20VS-3PFR20VS-4PFR20VS-5PFR20VS-6P

FR20PS的型号有;材质为:PP

FR20PS-1PFR20PS-2PFR20PS-3PFR20PS-4PFR20PS-5P

FR30HVS的型号有;材质为:CPVC

FR20HVS-1PFR20HVS-2PFR20HVS-3PFR20HVS-4PFR20HVS-5P

FR20S6:为316不锈钢.FR20S6L为316L不锈钢

NOHKEN日本能研连杆浮球开关FR30S系列

FR30S-1PFR30S-2PFR30S-3PFR30S-4PNOHKEN日本能研

日本能研FR30系列连杆液位开关FR20S-1PFR20S-2PFR20S-3PFR20S-4P

FR20S-1P日本NOHKEN日本能研连杆液位开关FR20S-2P

FR30S-1PFR30S-2PFR30S-3PFR30S-4PFR30S-5PFR30S-6P

FR30VS的型号有;材质为PVC

FR30VS-1PFR30VS-2PFR30VS-3PFR30VS-4PFR30VS-5PFR30VS-6P

FR30PS的型号有;材质为:PP

FR30PS-1PFR30PS-2PFR30PS-3PFR30PS-4PFR30PS-5P

FR30HVS-1PFR30HVS-2PFR30HVS-3PFR30HVS-4PFR30HVS-5P

FR30S6:为316不锈钢.FR30S6L为316L不锈钢

### 浮球参数

外径尺寸直径49\*H50

内径尺寸15.4mm材质SUS316

可测量液体的比重0.55以上

吃水25mm粘度5P

逆水性可以（注：球上下反转时，逆向工作的意思）

端子盒材质ADC12结构IP65电线接入口JISF20a

### 法兰

尺寸JIS5K50A材质SUS304

晶体管管座外径尺寸直径13.8

材质sus304L尺寸（Max）3950mm其它（温度）

zui大检测点7浮球耐压2MPA使用温度-10-100

L1尺寸（Min）50mmL-Ln50mm

设定间隔(Min)90mm

### 日本能研连杆液位开关FR系列

FR20S-1PFR20S-2PFR20S-3PFR20S-4P

内径尺寸15.4mm

材质SUS316

吃水25mm

粘度5P

逆水性可以（注：球上下反转时，逆向工作的意思）

端子盒

材质ADC12

结构IP65

电线接入口JISF20a

法兰尺寸JIS5K50A

材质SUS304 晶体管管座

外径尺寸直径13.8材质sus304

L尺寸 ( Max)3950mm

其它 ( 温度 )

zui大检测点7浮球耐压2MPA

使用温度-10-100

L1尺寸 ( Min)50mm

L-Ln50mm

NOHKEN能研连杆浮球液位开关系列FR型连杆式液位计 输出接点：磁簧开关 用途适合：水，油等一切净水器以及原油桶。技术水平/功能。能够达到高7点的警报能够控制电磁场以及水泵。

具体型号：FR20,FR30B,FR30S/FR60S FR10 FR30VS/FR60VS FR30PS/FR60PS FR30HVS/FR60HVS FH30 FH50