

日标方管JIS-G3466标准

产品名称	日标方管JIS-G3466标准
公司名称	上海创歌科技有限公司
价格	6020.00/吨
规格参数	材质:STKR400/490 执行标准:JIS-G3466-2010 长度:6/12米
公司地址	上海市松江区泗砖路103弄松江钢材城
联系电话	13671927581 13671927566

产品详情

日标方管JIS-G3466标准日标方矩管：一般强度船体结构用钢分为D4个等级的钢材的屈服强度（不小于235N/mm²）和抗拉强度（4-52N/mm²）一样，只是不同温度下的冲击功不一样而已.高强度船体结构用钢按其屈服强度划分强度等级，每一强度等级又按其冲击韧性的不同分为F1级。A3D3E3F32的屈服强度不小于315N/mm²,抗拉强度44-57N/mm²,F分别表示其各自可分别在：度、-2度、-4度、-6度的情况下所能达到的冲击韧性。日标矩形管尺寸表：20x20x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.12 KG/M)40x25x2MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (1.83 KG/M)20x20x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (1.35 KG/M)40x25x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.23 KG/M)25x25x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.43 KG/M)50x20x2MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (1.96 KG/M)25x25x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (1.74 KG/M)50x25x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.62 KG/M)25x25x3MM (SHS) SQUARE STEEL HOLLOW SECTION (2.04 KG/M)50x25x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.07 KG/M)30x30x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.68 KG/M)50x30x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.92 KG/M)30x30x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (2.14 KG/M)50x30x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.45 KG/M)30x30x3MM (SHS) SQUARE STEEL HOLLOW SECTION (2.51 KG/M)50x40x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.77 KG/M)40x40x2MM (SHS) SQUARE STEEL HOLLOW SECTION (2.31 KG/M)60x30x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.77 KG/M)日标方矩型管理重表：80x40x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (12.80 KG/M)70x70x3MM (SHS) SQUARE STEEL HOLLOW SECTION (6.28 KG/M)80x50x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (5.66 KG/M)70x70x3.6MM (SHS) SQUARE STEEL HOLLOW SECTION (7.46 KG/M)80x50x4MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.34 KG/M)70x70x5MM (SHS) SQUARE STEEL HOLLOW SECTION (10.11 KG/M)90x50x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (6.13 KG/M)70x70x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (12.50 KG/M)90x50x3.6MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.24 KG/M)70x70x8MM (SHS) SQUARE STEEL HOLLOW SECTION (15.30 KG/M)90x50x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (9.70 KG/M)80x80x3MM (SHS) SQUARE STEEL HOLLOW SECTION (7.22 KG/M)100x50x3MM (RHS)

RECTANGULAR STEEL HOLLOW SECTION (6.60 KG/M)80x80x3.6MM (SHS) SQUARE STEEL HOLLOW SECTION (8.59 KG/M)100x50x4MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.86 KG/M)80x80x5MM (SHS) SQUARE STEEL HOLLOW SECTION (11.70 KG/M)100x50x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (10.90 KG/M)80x80x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (14.40 KG/M)100x50x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (13.40 KG/M)80x80x8MM (SHS) SQUARE STEEL HOLLOW SECTION (17.80 KG/M)100x50x8MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (16.60 KG/M)90x90x3.6MM (SHS) SQUARE STEEL HOLLOW SECTION (9.72 KG/M)100x60x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.22 KG/M)90x90x5MM (SHS) SQUARE STEEL HOLLOW SECTION (13.30 KG/M)100x60x3.6MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.59 KG/M)90x90x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (16.40 KG/M)100x60x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (11.70 KG/M)100x60x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (14.40 KG/M)100x100x3MM (SHS) SQUARE STEEL HOLLOW SECTION (8.69 KG/M)100x60x8MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (17.80 KG/M)100x100x4MM (SHS) SQUARE STEEL HOLLOW SECTION (12.00 KG/M)120x60x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.01 KG/M)100x100x5MM (SHS) SQUARE STEEL HOLLOW SECTION (14.80 KG/M)120x60x3.6MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (9.72 KG/M)100x100x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (18.40 KG/M)120x60x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (13.30 KG/M)100x100x8MM (SHS) SQUARE STEEL HOLLOW SECTION (22.90 KG/M)120x60x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (16.40 KG/M)100x100x10MM (SHS) SQUARE STEEL HOLLOW SECTION (27.90 KG/M)120x80x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (14.80 KG/M)120x120x5MM (SHS) SQUARE STEEL HOLLOW SECTION (18.00 KG/M)120x80x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (18.40 KG/M)120x120x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (22.30 KG/M)120x80x8MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (22.9 KG/M)120x120x8MM (SHS) SQUARE STEEL HOLLOW SECTION (27.90 KG/M)120x80x10MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (27.9 KG/M)120x120x10MM (SHS) SQUARE STEEL HOLLOW SECTION (34.20 KG/M)150x75x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (16.37 KG/M)120x120x12.5MM (SHS) SQUARE STEEL HOLLOW SECTION (41.60 KG/M)

日标型钢：CPE属部分柏犁抗冲改性剂，价廉，抗冲击改性效果及耐候性也较好，还能降~PVC—C树脂的融体粘度，改善融体流动性，提高管材的挤出速度。但CPE类似固体增塑剂，会显降~PVC—C管材、管件的维软化温度；MBS，ABS属粒子分散犁抗冲改性剂，抗冲击改性效果好，对PVC~C管材、管件的维}软化温度影响也较小，但MBS，ABS分子链中含有饱和双键，耐候性较差，小适合户外使用：抗冲犁ACR及PVC / 高分性体接枝』L聚树脂分子链rf1 / 1含台 / 1饱和圾健，耐候性极好，抗冲改性也好，足较为理想的抗冲击改性剂，但价格较高。