

聊城日标方管JIS-G3466

产品名称	聊城日标方管JIS-G3466
公司名称	上海创歌科技有限公司
价格	5670.00/吨
规格参数	材质:STKR400/490 执行标准:JIS-G3466-2010 长度:6/12米
公司地址	上海市松江区泗砖路103弄松江钢材城
联系电话	13671927581 13671927566

产品详情

聊城日标方管JIS-G3466日标方矩管：一般在钢包中需进行脱氧及调整成份操作；然后在钢液表面抛上碳化稻壳防止钢水被氧化，即可送往连铸或模铸工区。对要求高的钢种可增加底吹氩、RH真空处理、喷粉处理（喷SI—CA粉及变性石灰）可以有效降低钢中的气体与夹杂，并有进一步降碳及降硫的作用。在这些炉外精炼措施后还可以*终微调成份，满足优质钢材的需求。初轧模铸钢锭采取热装、热送新工艺，进入均热炉加热，然后通过初轧机及钢坯连轧机轧成板坯、管坯、小方坯等初轧产品，经过切头、切尾、表面清理，（火焰清理、打磨）高品质产品则还需对初轧坯进行扒皮和探伤，检验合格后入库。日标矩形管尺寸表：20x20x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.12 KG/M)40x25x2MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (1.83 KG/M)20x20x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (1.35 KG/M)40x25x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.23 KG/M)25x25x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.43 KG/M)50x20x2MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (1.96 KG/M)25x25x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (1.74 KG/M)50x25x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.62 KG/M)25x25x3MM (SHS) SQUARE STEEL HOLLOW SECTION (2.04 KG/M)50x25x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.07 KG/M)30x30x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.68 KG/M)50x30x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.92 KG/M)30x30x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (2.14 KG/M)50x30x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.45 KG/M)30x30x3MM (SHS) SQUARE STEEL HOLLOW SECTION (2.51 KG/M)50x40x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.77 KG/M)40x40x2MM (SHS) SQUARE STEEL HOLLOW SECTION (2.31 KG/M)60x30x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.77 KG/M)日标方矩型管理重表：80x40x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (12.80 KG/M)70x70x3MM (SHS) SQUARE STEEL HOLLOW SECTION (6.28 KG/M)80x50x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (5.66 KG/M)70x70x3.6MM (SHS) SQUARE STEEL HOLLOW SECTION (7.46 KG/M)80x50x4MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.34 KG/M)70x70x5MM (SHS) SQUARE STEEL HOLLOW SECTION (10.11 KG/M)90x50x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (6.13 KG/M)70x70x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (12.50 KG/M)90x50x3.6MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.24 KG/M)70x70x8MM (SHS) SQUARE STEEL HOLLOW

SECTION (15.30 KG/M)90x50x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (9.70 KG/M)80x80x3MM (SHS) SQUARE STEEL HOLLOW SECTION (7.22 KG/M)100x50x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (6.60 KG/M)80x80x3.6MM (SHS) SQUARE STEEL HOLLOW SECTION (8.59 KG/M)100x50x4MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.86 KG/M)80x80x5MM (SHS) SQUARE STEEL HOLLOW SECTION (11.70 KG/M)100x50x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (10.90 KG/M)80x80x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (14.40 KG/M)100x50x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (13.40 KG/M)80x80x8MM (SHS) SQUARE STEEL HOLLOW SECTION (17.80 KG/M)100x50x8MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (16.60 KG/M)90x90x3.6MM (SHS) SQUARE STEEL HOLLOW SECTION (9.72 KG/M)100x60x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.22 KG/M)90x90x5MM (SHS) SQUARE STEEL HOLLOW SECTION (13.30 KG/M)100x60x3.6MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.59 KG/M)90x90x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (16.40 KG/M)100x60x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (11.70 KG/M)日标方矩管理论重量表：100x60x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (14.40 KG/M)100x100x3MM (SHS) SQUARE STEEL HOLLOW SECTION (8.69 KG/M)100x60x8MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (17.80 KG/M)100x100x4MM (SHS) SQUARE STEEL HOLLOW SECTION (12.00 KG/M)120x60x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.01 KG/M)100x100x5MM (SHS) SQUARE STEEL HOLLOW SECTION (14.80 KG/M)120x60x3.6MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (9.72 KG/M)100x100x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (18.40 KG/M)120x60x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (13.30 KG/M)100x100x8MM (SHS) SQUARE STEEL HOLLOW SECTION (22.90 KG/M)120x60x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (16.40 KG/M)100x100x10MM (SHS) SQUARE STEEL HOLLOW SECTION (27.90 KG/M)120x80x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (14.80 KG/M)120x120x5MM (SHS) SQUARE STEEL HOLLOW SECTION (18.00 KG/M)120x80x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (18.40 KG/M)120x120x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (22.30 KG/M)120x80x8MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (22.9 KG/M)120x120x8MM (SHS) SQUARE STEEL HOLLOW SECTION (27.90 KG/M)120x80x10MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (27.9 KG/M)120x120x10MM (SHS) SQUARE STEEL HOLLOW SECTION (34.20 KG/M)150x75x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (16.37 KG/M)120x120x12.5MM (SHS) SQUARE STEEL HOLLOW SECTION (41.60 KG/M)日标型钢：B33CLB38CL B42CL有良好冷成型性能，用于汽车滚型车轮轮网及轮幅。B44QZRB48QZR制造汽车传动轴管用。B32LB 55LB51LB42LB51DL汽车大梁、横梁用。锅炉及压力容器用钢Q/BQB32HII19Mn6DIN17155(EN128-2)HII(P 265GH)19Mn6(P355GH)除保证常温性能外，还保证较高温度下的力学性能，适用于蒸汽锅炉设备，较高工作温度的压力容器及类似结构件。