

# 莱芜日标矩形管执行标准

产品名称	莱芜日标矩形管执行标准
公司名称	上海创歌科技有限公司
价格	5450.00/吨
规格参数	材质:STKR400/490 执行标准:JIS-G3466-2010 长度:6/12米
公司地址	上海市松江区泗砖路103弄松江钢材城
联系电话	13671927581 13671927566

## 产品详情

莱芜日标矩形管执行标准日标方矩管：4氧化脱碳敏感性模具在加热过程中，如果产生氧化、脱碳现象，就会改变模具的形状和性能，影响模具的硬度、耐磨性和使用寿命，招致模具早期失效。有些钼含量高的模具钢，由于容易氧化、脱碳，有一段时间限制了其推广应用，直到热处理工艺装备发展以后，采用特种热处理工艺（如真空热处理，可控气氛热处理、盐浴热处理等）以后，能够避免氧化、脱碳，这类模具钢，才顺利得到推广应用。钼基合金虽然具有极为的高温性能，但是由于在高温下极易氧化，严重地限制了其应用范围。日标矩形管尺寸表：20x20x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.12 KG/M)40x25x2MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (1.83 KG/M)20x20x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (1.35 KG/M)40x25x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.23 KG/M)25x25x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.43 KG/M)50x20x2MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (1.96 KG/M)25x25x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (1.74 KG/M)50x25x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.62 KG/M)25x25x3MM (SHS) SQUARE STEEL HOLLOW SECTION (2.04 KG/M)50x25x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.07 KG/M)30x30x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.68 KG/M)50x30x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.92 KG/M)30x30x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (2.14 KG/M)50x30x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.45 KG/M)30x30x3MM (SHS) SQUARE STEEL HOLLOW SECTION (2.51 KG/M)50x40x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.77 KG/M)40x40x2MM (SHS) SQUARE STEEL HOLLOW SECTION (2.31 KG/M)60x30x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.77 KG/M)日标方矩型管理重表：80x40x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (12.80 KG/M)70x70x3MM (SHS) SQUARE STEEL HOLLOW SECTION (6.28 KG/M)80x50x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (5.66 KG/M)70x70x3.6MM (SHS) SQUARE STEEL HOLLOW SECTION (7.46 KG/M)80x50x4MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.34 KG/M)70x70x5MM (SHS) SQUARE STEEL HOLLOW SECTION (10.11 KG/M)90x50x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (6.13 KG/M)70x70x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (12.50 KG/M)90x50x3.6MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.24 KG/M)70x70x8MM (SHS) SQUARE STEEL HOLLOW SECTION (15.30 KG/M)90x50x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (9.70

KG/M)80x80x3MM (SHS) SQUARE STEEL HOLLOW SECTION (7.22 KG/M)100x50x3MM (RHS)  
RECTANGULAR STEEL HOLLOW SECTION (6.60 KG/M)80x80x3.6MM (SHS) SQUARE STEEL HOLLOW  
SECTION (8.59 KG/M)100x50x4MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.86  
KG/M)80x80x5MM (SHS) SQUARE STEEL HOLLOW SECTION (11.70 KG/M)100x50x5MM (RHS)  
RECTANGULAR STEEL HOLLOW SECTION (10.90 KG/M)80x80x6.3MM (SHS) SQUARE STEEL HOLLOW  
SECTION (14.40 KG/M)100x50x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (13.40  
KG/M)80x80x8MM (SHS) SQUARE STEEL HOLLOW SECTION (17.80 KG/M)100x50x8MM (RHS)  
RECTANGULAR STEEL HOLLOW SECTION (16.60 KG/M)90x90x3.6MM (SHS) SQUARE STEEL HOLLOW  
SECTION (9.72 KG/M)100x60x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.22  
KG/M)90x90x5MM (SHS) SQUARE STEEL HOLLOW SECTION (13.30 KG/M)100x60x3.6MM (RHS)  
RECTANGULAR STEEL HOLLOW SECTION (8.59 KG/M)90x90x6.3MM (SHS) SQUARE STEEL HOLLOW  
SECTION (16.40 KG/M)100x60x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (11.70  
KG/M)日标方矩管理论重量表：100x60x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (14.40  
KG/M)100x100x3MM (SHS) SQUARE STEEL HOLLOW SECTION (8.69 KG/M)100x60x8MM (RHS)  
RECTANGULAR STEEL HOLLOW SECTION (17.80 KG/M)100x100x4MM (SHS) SQUARE STEEL HOLLOW  
SECTION (12.00 KG/M)120x60x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.01  
KG/M)100x100x5MM (SHS) SQUARE STEEL HOLLOW SECTION (14.80 KG/M)120x60x3.6MM (RHS)  
RECTANGULAR STEEL HOLLOW SECTION (9.72 KG/M)100x100x6.3MM (SHS) SQUARE STEEL HOLLOW  
SECTION (18.40 KG/M)120x60x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (13.30  
KG/M)100x100x8MM (SHS) SQUARE STEEL HOLLOW SECTION (22.90 KG/M)120x60x6.3MM (RHS)  
RECTANGULAR STEEL HOLLOW SECTION (16.40 KG/M)100x100x10MM (SHS) SQUARE STEEL  
HOLLOW SECTION (27.90 KG/M)120x80x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (14.80  
KG/M)120x120x5MM (SHS) SQUARE STEEL HOLLOW SECTION (18.00 KG/M)120x80x6.3MM (RHS)  
RECTANGULAR STEEL HOLLOW SECTION (18.40 KG/M)120x120x6.3MM (SHS) SQUARE STEEL  
HOLLOW SECTION (22.30 KG/M)120x80x8MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (22.9  
KG/M)120x120x8MM (SHS) SQUARE STEEL HOLLOW SECTION (27.90 KG/M)120x80x10MM (RHS)  
RECTANGULAR STEEL HOLLOW SECTION (27.9 KG/M)120x120x10MM (SHS) SQUARE STEEL HOLLOW  
SECTION (34.20 KG/M)150x75x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (16.37  
KG/M)120x120x12.5MM (SHS) SQUARE STEEL HOLLOW SECTION (41.60 KG/M)日标型钢：为了再选尾  
矿，从原生产系统一直到尾矿坝干坡段，建立了6个尾矿再选回收点，年产精矿13万t，东鞍山磁铁矿不  
易被塔尔油和氧化石蜡皂吸附上来，造成磁铁矿大部分留在尾矿中，现已投资2万元，建立了2个尾矿再  
选加收点，年产精矿3万t，其工艺流程见图12。鞍钢齐大山选矿厂尾矿再选厂齐大山铁矿以假象和半假  
象赤铁矿为主，与大孤山.东鞍山铁矿石对比，其铁矿物嵌布粒度较粗，尾矿品味为1%--13%.齐大山选矿  
厂至今已投资8万元，建立了6个尾矿再选回收点，全部采用在尾矿输送管道下部旁接支管截流尾矿，采  
用一段粗选.二段精选的重选工艺，获得\*终精矿。