

湖州日标方矩管大口径系列

产品名称	湖州日标方矩管大口径系列
公司名称	上海创歌科技有限公司
价格	6040.00/吨
规格参数	材质:STKR400/490 执行标准:JIS-G3466-2010 长度:6/12米
公司地址	上海市松江区泗砖路103弄松江钢材城
联系电话	13671927581 13671927566

产品详情

湖州日标方矩管大口径系列 日标方矩管：古人类在用火方面素有传统。*迟在46万年前的北京猿人时期，我们的祖先已学会了用火。已有的考古资料表明，北京周口店山顶洞人居住的洞穴中发现的灰烬，是世界公认的具有**的人类用火的*早遗迹之一。古代先民将火用于材料热处理是从新石器时代开始的。在新石器时代早期，古代先民在劳动和生活中，经常与泥土打交道，发现泥土与适量的水混合后，就会有粘性和可塑性，可以用手随意地塑造成各种形状。泥坯凉干变硬，可盛东西，但泥器怕水。

日标矩形管尺寸表：20x20x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.12 KG/M) 40x25x2MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (1.83 KG/M) 20x20x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (1.35 KG/M) 40x25x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.23 KG/M) 25x25x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.43 KG/M) 50x20x2MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (1.96 KG/M) 25x25x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (1.74 KG/M) 50x25x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.62 KG/M) 25x25x3MM (SHS) SQUARE STEEL HOLLOW SECTION (2.04 KG/M) 50x25x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.07 KG/M) 30x30x2MM (SHS) SQUARE STEEL HOLLOW SECTION (1.68 KG/M) 50x30x2.5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (2.92 KG/M) 30x30x2.5MM (SHS) SQUARE STEEL HOLLOW SECTION (2.14 KG/M) 50x30x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.45 KG/M) 30x30x3MM (SHS) SQUARE STEEL HOLLOW SECTION (2.51 KG/M) 50x40x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.77 KG/M) 40x40x2MM (SHS) SQUARE STEEL HOLLOW SECTION (2.31 KG/M) 60x30x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (3.77 KG/M) 日标方矩型管理重表：80x40x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (12.80 KG/M) 70x70x3MM (SHS) SQUARE STEEL HOLLOW SECTION (6.28 KG/M) 80x50x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (5.66 KG/M) 70x70x3.6MM (SHS) SQUARE STEEL HOLLOW SECTION (7.46 KG/M) 80x50x4MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.34 KG/M) 70x70x5MM (SHS) SQUARE STEEL HOLLOW SECTION (10.11 KG/M) 90x50x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (6.13 KG/M) 70x70x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (12.50 KG/M) 90x50x3.6MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.24 KG/M) 70x70x8MM (SHS) SQUARE STEEL HOLLOW SECTION (15.30 KG/M) 90x50x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (9.70 KG/M) 80x80x3MM (SHS) SQUARE STEEL HOLLOW SECTION (7.22 KG/M) 100x50x3MM

(RHS) RECTANGULAR STEEL HOLLOW SECTION (6.60 KG/M) 80x80x3.6MM (SHS) SQUARE STEEL HOLLOW SECTION (8.59 KG/M) 100x50x4MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.86 KG/M) 80x80x5MM (SHS) SQUARE STEEL HOLLOW SECTION (11.70 KG/M) 100x50x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (10.90 KG/M) 80x80x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (14.40 KG/M) 100x50x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (13.40 KG/M) 80x80x8MM (SHS) SQUARE STEEL HOLLOW SECTION (17.80 KG/M) 100x50x8MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (16.60 KG/M) 90x90x3.6MM (SHS) SQUARE STEEL HOLLOW SECTION (9.72 KG/M) 100x60x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (7.22 KG/M) 90x90x5MM (SHS) SQUARE STEEL HOLLOW SECTION (13.30 KG/M) 100x60x3.6MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.59 KG/M) 90x90x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (16.40 KG/M) 100x60x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (11.70 KG/M) 日标方矩管理论重量表 : 100x60x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (14.40 KG/M) 100x100x3MM (SHS) SQUARE STEEL HOLLOW SECTION (8.69 KG/M) 100x60x8MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (17.80 KG/M) 100x100x4MM (SHS) SQUARE STEEL HOLLOW SECTION (12.00 KG/M) 120x60x3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (8.01 KG/M) 100x100x5MM (SHS) SQUARE STEEL HOLLOW SECTION (14.80 KG/M) 120x60x3.6MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (9.72 KG/M) 100x100x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (18.40 KG/M) 120x60x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (13.30 KG/M) 100x100x8MM (SHS) SQUARE STEEL HOLLOW SECTION (22.90 KG/M) 120x60x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (16.40 KG/M) 100x100x10MM (SHS) SQUARE STEEL HOLLOW SECTION (27.90 KG/M) 120x80x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (14.80 KG/M) 120x120x5MM (SHS) SQUARE STEEL HOLLOW SECTION (18.00 KG/M) 120x80x6.3MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (18.40 KG/M) 120x120x6.3MM (SHS) SQUARE STEEL HOLLOW SECTION (22.30 KG/M) 120x80x8MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (22.9 KG/M) 120x120x8MM (SHS) SQUARE STEEL HOLLOW SECTION (27.90 KG/M) 120x80x10MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (27.9 KG/M) 120x120x10MM (SHS) SQUARE STEEL HOLLOW SECTION (34.20 KG/M) 150x75x5MM (RHS) RECTANGULAR STEEL HOLLOW SECTION (16.37 KG/M) 120x120x12.5MM (SHS) SQUARE STEEL HOLLOW SECTION (41.60 KG/M) 日标型钢 : PonyMill轧机为单机架4辊轧机,并在入口区配备开卷机和夹送辊以及在出口区配有卷取机。该设备所需要的投资费用为3500万美元,投资回收期预计少于2.5年。目前该技术正处于试验阶段。意大利达涅利设备公司开发出超薄热轧带钢生产新设备f2C R以无头或半无头形式生产超薄热轧带钢时由于轧制时间长,加到工作辊上的热应力和机械应力大,所以对带钢凸度和平直度控制标准提出了更严格的要求。为此,意大利达涅利设备公司经过多年研究,成功开发出一种轧机机架的新概念,即灵活凸度和自由轧制机架。