微型流量计，氧气流量计，氮气流量计，广州微小流量计报价

产品名称	微型流量计，氧气流量计，氮气流量计，广州微小流量计报价
公司名称	广州迪川仪器仪表有限公司
价格	1600.00/台
规格参数	
公司地址	广州市番禺区石基镇前锋南路31号
联系电话	86-02085628522/85550363 13539727793

产品详情

型号:FS 品牌 迪川仪表 测氮气流量计| 氮气流量计价格|气体流量计|气体流量计原理|气体质量流量计 小型气体流量计|氧气流量计价格|气体流量传感器|空气流量计传感器|氮气传感器|微小型气体流量计 FS列是采用世界领先的美国微机电系统（MEMS）流量传感技术和智能电子控制技术，专为普通气体流量监测开发的产品。 该传感器能直接测量气体质量流量，压损低。适用于净化空气或氮气流量，还可用于环保监测仪器，如空气采样 我们MF4008 MF4003 MF5712
MF5706一体显示微型流量计如果有什么可以登录官网 http:www.gz-dichuan.com 或来电咨询
TEL:020-85628522 85550363 FAX:020-85628533 产品概述: FS4003流量传感器，管道内径为3mm，成本低测量范围最大到5SLPM；适用于粒子计数器和各类分析仪器。
FS4008流量传感器，管道内径为8mm，测量范围最大到50SLPM； 产品特点: -
专为管径3mm和8mm的气管中的低压气体流量测量而设计 - 支持多种连接方式，易于安装与使用
- 传感芯片采用热质量流量计量，无需温度压力补偿，保证了传感器的高精度计量 -
在单个芯片上实现了多传感器集成，使其量程比达到了100:1甚至更高 - 输出方式灵活，既可通过通讯接口主动上传数据或由上位机查询输出数据，也可通过模拟接口输出线性的模拟电压 -
零点稳定度高 - 全量程高稳定性、高精确度和优良的重复性 - 低功耗、低压损 -
响应速度快 产品特点:

性能参数 FS4003 FS4008 单位 通 径 3 8 mm 最大流量 2, 3, 4, 5 10, 20, 30, 40, 50 SLPM 量程比 100:1 精 度 ±(1.5+0.2FS) % 重复性 0.75 % 零点输出飘移 ±30 mV 输出飘移 0.12 %/oC 响应时间 100 ms 工作电源 8~18Vdc,100mA 输出方式 线性，RS232/模拟电压0.5~4.5Vdc 最大流量压损 100 600 pa
最大工作压力 0.5 MPa 工作温度 -10 ~ +55 oC 存储温度 -20 ~ +65 oC 工作湿度
<95%RH（无结冰、无凝露） 机械接口 BSPT1/4(R1/4),4mm/6mm/8mm快速接头 校准方式
空气（或其他气体），20oC，101.325kPa 重量 57（带R1/4,BSPT1/4接口）
71(带4mm，8mm快速接口，68（带6mm快速接头) 英文说明 Unit performance parameters FS4003 FS4008 3 8 mm diameter Maximum flow 2, 3, 4, 5 10, 20, 30, 40, 50 SLPM 100:1 turndown ratio Accuracy ± (1.5 +0.2 FS)% Repeatability 0.75% Zero drift ± 30 mV Output drift 0.12% / oC Response time 100 ms Power Supply 8 ~ 18Vdc, 100mA Linear output, RS232 / analog voltage 0.5 ~ 4.5Vdc Maximum flow pressure loss 100 600 pa Maximum working pressure of 0.5 MPa Operating temperature -10 ~ +55 oC Storage temperature -20 ~ +65 oC Humidity <95% RH (with no icing or condensation) Mechanical interface BSPT1 / 4 (R1 / 4), 4mm/6mm/8mm quick

connector Calibration methods of air (or other gases), 20oC, 101.325kPa Weight of 57 (with R1 / 4, BSPT1 / 4 interface) 71 (with 4mm, 8mm fast interface, 68 (with 6mm quick connector)