

Selar PA 3426 (尼龙阻隔树脂)

产品名称	Selar PA 3426 (尼龙阻隔树脂)
公司名称	东莞市中源塑胶原料有限公司
价格	.00/件
规格参数	品牌:杜邦 型号:3426 性能:尼龙阻隔树脂
公司地址	东莞市樟木头镇樟罗社区先威路76号塑金塑胶商业中心11号商业
联系电话	15118326922 15118326922

产品详情

Selar PA 3426

Polyamide 6I/6T Copolymer

DuPont Packaging & Industrial Polymers

产品说明 :

Selar PA 3426 is an amorphous nylon (polyamide) resin which exhibits superior transparency, good barrier properties to gases, water, solvents and essential oils and high temperature structural properties which make it suitable for consideration in a number of applications.Features:

Selar PA 3426 barrier resin can be utilized in both flexible and rigid packaging structures and is characterized by very good gas O₂, CO₂ and moisture barrier. Furthermore, Selar PA is unique in that its gas barrier improves with increasing relative humidity. It has excellent physical properties, high temperature resistance and excellent optical properties desirable in a structural resin. Like other nylons, Selar PA barrier resin is an excellent barrier for many types of solvent systems. In general it has good resistance to aliphatic, aromatic hydrocarbons, dilute alkalis, higher molecular weight alcohols, and low concentrations of lower molecular weight alcohols. It is not recommended for acids or concentrated lower molecular weight alcohols. End use testing is recommended for each application. With its high degree of stiffness, very good gas and moisture barrier, solvent resistance and excellent gloss and clarity, Selar PA used in monolayer provides a "glass like" container for rigid packaging.

Applications:

High melt viscosity for extrusion processes such as EBM.

Improved performance in shrink applications when blended with nylon 6.

Monolayer - blow molded tubes, pharmaceutical vials or bottles, typically less than 4 ounces.

Nylon 6 modification for higher heat resistance, better oxygen barrier, broader thermoforming window.

物性信息：

基本特信息	耐热性，高清晰度，高阻隔树脂	
用途	包装薄膜管件混合瓶子小瓶	
机构评级	FDA 21 CFR 177.1500(a)(12)FDA 21 CFR 177.1500(b)(12)	
形式	粒子	
物理性能额定值单位制测试方法		1.19
固有粘度		0.82
含水量 1		
玻璃转化温度单位制测试方法		125
注射成型温度		240 到 250

注射说明 Processing Temperature: 310 ° C (590 ° F)

备注

供应PA66 3426 美国杜邦 汽车油杯料 耐热阻隔树脂

供应PA66 ST801 美国杜邦 ST811杰出的耐冲击性，耐寒，耐高温，增韧级

供应PA66 ST801A 美国杜邦 超韧级，防紫外线

供应PA66 103HSL 美国杜邦 热稳定级 耐高温

供应PA66 103FHS 美国杜邦 热稳定级

供应PA66 42A 美国杜邦 高粘性

供应PA66 W5053 美国杜邦 高粘性 粘度45%

供应PA66 FR50 美国杜邦 加GF25% V-0阻然

供应PA66 101F 美国杜邦 中粘度，通用级