

# 自粘B35A270宝钢电工钢

产品名称	自粘B35A270宝钢电工钢
公司名称	上海钰源国际贸易有限公司
价格	8.60/千克
规格参数	材质:B35A270 产地:宝钢 厚度:0.35mm
公司地址	上海市宝山区梅林路358号13幢（注册地址）
联系电话	13636459805

## 产品详情

牌号公称厚度 (mm)密度 (kg/dm<sup>3</sup>)\*大铁损P15/50 (W/kg)\*小磁感B50 (T)\*小叠片系数 (%) B35A2100.3  
57.602.101.6295.0B35A2307.602.301.6295.0B35A2507.602.501.6295.0B35A2707.652.701.6295.0B35A3007.653.001.62  
95.0B35A3607.653.601.6395.0B35A4407.704.401.6495.0B35A5507.755.501.6495.0B50A2300.507.602.301.6296.0B50  
A2507.602.501.6296.0B50A2707.602.701.6296.0B50A2907.602.901.6296.0B50A3107.653.101.6296.0B50A3507.653.50  
1.6296.0B50A4007.654.001.6396.0B50A4707.704.701.6496.0B50A6007.756.001.6696.0B50A7007.807.001.7096.0B50  
A8007.808.001.7096.0B50A10000.657.8510.001.7096.0B50A13007.8513.001.7096.0B65A4707.653.701.7097.0B65A60  
07.754.701.7097.0B65A7007.754.901.7097.0B65A8007.808.001.7097.0B65A10007.8010.001.7097.0B65A13007.8513.0  
01.7097.0AH系列

牌号公称厚度 (mm)密度 (kg/dm<sup>3</sup>)\*大铁损P15/50 (W/kg)\*小磁感B50 (T)\*小叠片系数 (%) B35AH2300  
.357.652.301.6695.0B35AH2507.652.501.6795.0B35AH3007.703.001.6995.0B50AH3000.507.653.001.6796.0B50AH3  
507.703.501.7096.0B50AH4707.754.701.7296.0B50AH6007.756.001.7296.0B50AH8007.808.001.7496.0B50AH10007.  
8510.001.7596.0

注：a. 检测依据GB/T3655-2008。 b. 检测试样纵横向各半。 c. 对于消除应力退火高效无取向电工钢AR系列产品的磁性能测试仅适用于试样在750 下，经2小时消除应力退火后的状态。 d. P15/50表示在\*大磁感应强度为1.5T，频率为50Hz时，单位kg试样的铁芯损耗。 P10/400表示在\*大磁感应强度为1.0T，频率为400Hz时，单位kg试样的铁芯损耗。 e. B50表示对应于磁场强度为5000A/m时的磁感应强度。

典型电磁性能A系列牌号公称厚度 (mm)密度 (kg/dm<sup>3</sup>)\*大铁损 (W/kg)\*小磁感(T)P10/50P15/50P10/60P15/60  
B10B25B50B100B35A2300.357.600.922.151.152.671.471.571.661.78B35A2507.600.982.251.222.781.481.571.661.78B3  
5A2707.651.002.301.242.821.481.581.671.79B35A3007.651.142.531.423.131.511.591.681.80B35A3607.651.252.801.55  
3.411.511.601.681.80B35A4407.701.353.001.663.691.531.621.701.82B35A5507.751.443.501.924.341.531.611.691.81B5  
0A2500.507.601.052.391.343.031.481.571.671.79B50A2707.601.082.501.403.181.481.571.671.80B50A2907.601.102.60  
1.413.251.491.581.671.79B50A3107.651.182.701.573.381.501.591.681.80B50A3507.651.352.851.653.601.501.601.681.

80B50A4007.651.45\*\*\*\*1.844.011.521.611.691.81B50A4707.701.764.002.225.011.521.601.691.80B50A6007.751.934.3  
02.435.371.531.621.711.82B50A7007.802.425.203.016.471.561.651.731.84B50A8007.802.675.703.347.111.571.661.741  
.84B50A10007.852.826.203.577.801.591.681.761.87B50A13007.853.327.204.209.121.591.681.761.88B65A4700.657.65  
1.693.702.194.751.521.621.711.82B65A6007.752.114.702.715.971.521.621.711.82B65A7007.752.194.902.846.251.531.  
631.721.83B65A8007.802.695.903.427.521.561.661.741.85B65A10007.802.856.403.678.171.571.671.751.86B65A13007  
.853.257.404.228.521.591.681.771.88