

流平剂 H-633

产品名称	流平剂 H-633
公司名称	江西海多化工有限公司
价格	150.00/公斤
规格参数	
公司地址	江西省九江市永修县杨家岭星火工业园天虹路6号
联系电话	0792-3170318 13870276182

产品详情

cas：67762-85-0

化学成份：聚醚改性有机聚硅氧烷

性能特点

：优良的有机硅表面助剂。通过降低涂料表面张力以提高底材的润湿性。增加表面滑爽及耐划伤性和防粘连性，改善流平、提高光泽度、防止贝纳德旋涡。适用于溶剂型、无溶剂型及水性体系的涂料中添加。

物化数据及指标：

外观：无色至浅琥珀色透明油状液体

粘度（25℃）cs：800～1200

密度（25℃）g/cm3：1.03～1.04

浊点（25℃ 1%水溶液）：36～44

使用方法

水性体系（水性颜料、涂料、乳胶漆、水性油墨、中性墨水）：推荐用量总配方的0.3～1%

油性体系：推荐用量总配方的0.05～0.5%

无溶剂体系：推荐用量总配方的0.3～1%

在生产过程中的任何阶段加入，为了使用方便，可先用合适的溶剂稀释。

包 装： 本品包装规格为25l,200l或 i b c 塑桶、铁桶或按用户要求定制。

贮 运：按非危险化学品运输。阴凉干燥密封贮存。保质期12个月。

h-633 leveling agent

polyether modified polysiloxane

cas : 67762-85-0

features

h-633 leveling agent is effective at low concentrations. the amount required depends on the type of formulation, provides slip, gloss enhancement, , pigment treatment and leveling for ink and coatings applications. provides mar resistance for coatings applications

typical properties

appearance clear-to-hazy amber liquid

specific gravity at 25 ° c (77 ° f) 1.03-1.04

viscosity at 25 ° c (77 ° f) cs 800-1200

cloud point ° c (1%water solution):43-45

h-633 additive has been successful in these industrial applications1:

to improve leveling:

water-based (ink, industrial coating , paint) at 0.05-1% (based on solids)

solvent-based (plastic coating paint) at 0.05-0.5%

solvent-free paint at 0.3 -1%

f-333 additive can be added during the grind or let-down, or can be post-added.

characteristics may vary when used with different systems and formulations. thorough preproduction testing is necessary to ensure expected performance.

packaging & storage : 25l,200l plastic drum or ibc。 store in seal drum at room , dry place , usable life 1 year.

