

# 工业用超大鼓风干燥箱 鼓风烘箱

产品名称	工业用超大鼓风干燥箱 鼓风烘箱
公司名称	鑫磊实验仪器有限公司
价格	.00/台
规格参数	
公司地址	河北省沧州市运河区朝阳西路158号
联系电话	13613276395

## 产品详情

[工业用鼓风干燥箱 \( Industrial use drum wind drying oven \)](#)

用途概述(Uses Overview)：

[适用于工矿企业、科研院所医药卫生等单位实验室做干燥、烘培、熔腊、热处理之用。](#)

产品特点(Features)：

- [1、外壳采用优质冷轧钢制做，表面经静电喷涂工艺处理，造型美观大方，防腐耐用。](#)
- 2、工作室采用法纹不锈钢板或优质钢板加工成形并经过防腐处理，配以可调节式电抛光搁板，四角成半圆弧，便于清洁。
- 3、双开门设计，牢固耐用，两侧加热安全可靠，外型美观、开启方便、占地空间小，是工厂车间加工制造、办公实验的理想选择。
- 4、双门双层矩形观察窗，工作室内存品搁板高度可调，观察清晰，使用方便。
- 5、可选装微电脑，数字显示控温仪表。
- 6、微电脑智能控温仪，具有定时、超温报警、双屏显示功能、读数方便、控温精确。
- 7、配有漏电保护装置（选配）保证了工作人员和实验物品的安全。
- 8、独立的报警指示系统，干燥箱温度超过负荷自动停止，箱门可视窗外层玻璃温度符合欧洲安全标准，保证实验安全运行，确保人员安全。

- 9、良好的隔热设计，能长期高温运行，使用寿命长，便于更换，最大程度做到绿色、节能、环保。
- 10、全方位立体加热技术，确保工作室具有良好的温度均一性。
- 11、采用耐高温硅胶密封条，配以锁扣式松紧调节门锁，确保良好的密封性，防止热量流失。
- 12、独特的几何腔体洁净设计，保证对样品主动完美的保护。
- 13、传承美学设计理念，展现豪华典雅的仪器造型。

主要技术参数 ( The main technical parameters )

型号 ( Model )	DGF-2A	DGF-2AB	DGF-3A	DGF-3AB	DGF-4A	DGF-4AB
<a href="#">电源电压</a> ( Supply voltage )	220V/380V					
<a href="#">控温范围</a> ( Temperature range )	室温 (At room temperature) +10-250					
温度波动度 ( Temperature fluctuation )	± 1					
<a href="#">加热功率</a> ( Heating power )	6KW					
搁板负荷 ( Shelf load )	25KG					
工作室尺寸 ( Studio size ) mm ( 深 × 宽 × 高 ) ( D × W × H )	530 × 580 × 800		700 × 700 × 900		800 × 800 × 1000	
外形尺寸 ( Dimensions ) mm ( 深 × 宽 × 高 ) ( D × W × H )	630 × 810 × 1190		830 × 910 × 1290		930 × 1010 × 1390	

[\(注；A为镀锌板内胆，AB为不锈钢内胆。\)](#)  
(note: A is galvanized sheet bladder, AB for stainless steel inner.)

Uses Overview ( 用途概述 )：

Applicable to industrial and mining enterprises, scientific research institutes, medicine and health, and other units laboratory, baking, dry melt la, heat treatment with.

## Features ( 产品特点 ) :

1, the shell adopts the high quality cold-rolled steel do, surface of electrostatic spraying process, modelling beautiful and easy, corrosion and durable.

2, the studio of stainless steel plate grain or high qualified steel plate processing forming and antiseptic processing, match with adjustable electrolytic polishing shelf, four corners into half arc, facilitate clean.

3, double open the door design, durable, two side heating safe, reliable, and beautiful outlook, opens conveniently, covers an area of the space is little, is the factory workshop processing manufacturing, office of the ideal choice.

4, two-door double rectangular Windows, work indoor test product shelf height adjustable, observation is clear and easy to use.

5, can supply microcomputer, digital display control h<sub>2</sub>s table.

6, microcomputer intelligent control thermometer, has the timing, super temperature alarming, double screen function, reading convenient, temperature control precision.

7, equipped with leakage protection devices (optional) ensures the staff and test items safety.

8, independent alarm indicator system, drying oven temperature over load automatically stop, the outer glass temperature can be Windows with European safety standards and to ensure the safe operation, ensure the safety of operator.

9, good heat insulation design, a long-term high temperature operation, long service life, convenient to replace, the greatest degree do green, the energy conservation, the environmental protection.

10 and all-round stereo heating technology, to ensure that the studio has good temperature uniformity.

11, use high temperature resistant silicon sealing strip, match with lock type adjust tightness locks, ensure good sealing, prevent heat loss.

12, unique geometrical recessed clean design, to ensure that the sample of the active perfect protection.

13, inheritance aesthetics design concept, show the luxurious and elegant modelling of the instrument.