

光敏PT 3528 SMD 透明光敏 自然光感应

| | |
|------|--------------------------|
| 产品名称 | 光敏PT 3528 SMD 透明光敏 自然光感应 |
| 公司名称 | 深圳市凯升辉电子科技有限公司 |
| 价格 | 1.00/个 |
| 规格参数 | |
| 公司地址 | 深圳市宝安区航城街道九华科技园1栋2楼 |
| 联系电话 | 15999651139 |

产品详情

????????????2835????????????????????

???Features

??????Fastresponse times??

?????Highphoto sensitivity??

?????Smalljunction capacitance??

????CDS????????????????????ROHS?????Instead of the traditional CDS photosensitive resistance, containcadmium, lead and hazardous substances, ROHScompliant??

??Dedicated to the anti-IR interference products, controls the switching of day and night, without adding casing, filters??

?????Electro-Optical characteristics(Ta=25?)

| 参数 Parameter | 符号Symbol | 条件Condition | 小值Min. | 中间值Typ. | 大值Max. |
|---|----------|-----------------------|--------|---------|--------|
| 集电极发射极击穿电压Collector-Emitter Breakdown Voltage | BVCEO | Ic=100 μ A Ev=0Lux | 8 | --- | V |
| 发射极集电极击穿电压Emitter-Collector Breakdown Voltage | VECO | IE=100 μ A | 5 | | |
| 集电极发射极饱和电压Collector-Emitter Saturation Voltage | VCE(sta) | Ic=15mA Ev=200Lux | 1 | | |
| 启动延时Rise time | Tr | VCE=5V Ic=1mA | 4.5 | μ S | |

| | | | | | |
|---------------------------------------|--------|----------|-----|-----|--|
| 关闭延时Fall Time | Tf | RL=1000 | | | |
| 集电极暗电流Collector Dark Current | ICEO | Ev=0Lux | 500 | nA | |
| | | VCE=5V | | | |
| 导通状态集电极电流On State Collector Current | IC(on) | Ev=10Lux | 10 | μ A | |
| | | VCE=5v | | | |
| | | Ev=20Lux | 20 | | |
| 峰值灵敏度的波长Wavelength of PeakSensitivity | | --- | 520 | nm | |
| 光谱带宽范围Rang of Spectral Bandwidth | 0.5 | 400 | 700 | | |