

# 德国莱宝真空泵油LVO100

产品名称	德国莱宝真空泵油LVO100
公司名称	上海沪沁仪器设备有限公司
价格	750.00/桶
规格参数	
公司地址	上海市闵行区颛兴路639弄37号
联系电话	021-60449810

## 产品详情

德国莱宝真空泵油LVO100主要用于莱宝双级真空泵D系列。包装 5L 20L 208L

### 产品特点

LEYBONOL mineral oils are products distilled and refined from crude oil. These do not consist of precisely defined compounds but rather consist of a complex mixture. The way in which the mineral oil is pre-treated and its composition is decisive as to the applications it will be suited for. Depending on the distribution of the hydrocarbons and the dominance of certain properties, mineral oils are grouped according to paraffin-base, naphthenic and aromatic. For the purpose of attaining especially low ultimate pressures, mineral oils must be selected on the basis of a core fraction.

The thermal and chemical resistance of mineral oils has been found to be adequate in the majority of applications. They offer a high degree of compatibility with elastomers and resistance to hydrolysis

Oil Type	Description	Product examples	ISO VG class	Viscosity at 40 ° C
L VO 10 0	Mineral oil, free of additives	TRIVAC	ISO VG 100 (ca.)	mm2/s 10,5
L VO 110	Hydrocracked mineral oil with additives	E+DK RUVAC SOGEVAC (FC)	SV 65 A & SV65 BI 32	ISO VG at 40 ° C mm2/s 5,5
L	Mineral oil with additives	SOGEVAC A Series	SV 65, B Series	ISO VG at 40 ° C mm2/s

VO 120		SV 25 B, SV 65 BI (FC)	32	mm <sup>2</sup> /s	5,5
L	Mineral oil with additives	SOGEVAC SV 100, SV 40 B	ISO VG 68	at 40 ° C	mm <sup>2</sup> /s 9
VO 130					
L	Mineral oil with additives	SOGEVAC A Series SV 65, B Series	ISO VG	at 40 ° C	mm <sup>2</sup> /s
VO 140		SV 25 B, SV 65 BI (FC)	32	mm <sup>2</sup> /s	5
L	Mineral oil with additives	SOGEVAC SV 100, SV 40 B	ISO VG	at 40 ° C	mm <sup>2</sup> /s
VO 150			68	mm <sup>2</sup> /s	8
L	Hydrocracked mineral oil with additives	SOGEVAC SV 100, SV 40 B	ISO VG 68	at 40 ° C	mm <sup>2</sup> /s
VO 160				mm <sup>2</sup> /s	9