

粘土稳定剂

产品名称	粘土稳定剂
公司名称	河南省铭泰化工有限公司
价格	12000.00/吨
规格参数	
公司地址	河南省濮阳市台前县铭泰工业区
联系电话	03932216206

产品详情

粘土稳定剂属季产品，能有效地吸附在粘土表面，防止水敏性矿物水化膨胀及分散运移而对油气层造成的伤害，具有适用范围广、长久有效、用法简单、用量少、抗酸液、盐液、碱液和油水的冲刷等特点。

适用于活性水、射孔液、压裂液、钻井液及酸化液等入井工作液体。二．质量指标（执行标准Q/SYC-104-2007）名称粘土稳定剂 型号

外观淡黄色至棕红色液体淡黄色粘稠液体无色或淡黄色固体 密度（20℃，g/cm³） 1.00~1.15 1.00~1.15 1.05~1.20 pH值（1%） 6.0~9.0 6.0~9.0 5.0~8.0 固含量(%) 10 45 85 防膨率(%) 90 90

90三．使用方法² 根据地层粘土含量情况，使用浓度0.25%~0.50%。²

直接加入工作液中，循环均匀即可。四、包装、运输和贮存²

和 型塑料桶包装，每桶净重(200±0.5)kg或(25±0.5)kg； 型(25 kg±0.2)kg编织袋包装。²

通风贮存、防止曝晒，自生产之日起贮存期2年。本产品为新型复合型粘土稳定剂，由阳离子聚合物和无机盐复合而成，其中的有效成分通过中和或减少粘土表面电性达到抑制粘土水化膨胀的目的。该产品能有效地抑制地层粘土的水化膨胀，防止粘土矿物分散运移，防止地层伤害。本产品与盐酸、土酸配伍性好，是压裂、酸化、解堵及修井等井下作业的添加剂。 [性能指标] 项目 指标 外观

淡黄色固体或棕色液体 PH值 5.0~7.0 水溶性 与水互溶 防膨率% 80 [使用方法] 本产品略显酸性，使用时应配戴橡胶手套。不要与阴离子表面活性剂混合使用，用量随地层中粘土的类型、含量而变化，在一般情况下，常用的加量为1~2%。 [包装、贮运及注意事项] 包装：三合一包装袋，25kg/袋。运输：运输时应避免野蛮装卸，防止包装破损。贮存：置于阴凉通风干燥处保存。

Clay stabilizer is a quaternary amine, can effectively adsorb on the surface of clay, prevent water sensitivity mineral hydration swelling and dispersion migration of reservoir damage, with a wide range of application, long and effective, is easy to use, less dosage, anti-acid, salt solution, alkali solution and water washout characteristics. Applicable to active water, perforating fluid, fracturing fluid, drilling fluid into the well and acidizing fluid as working fluid. Two. Quality index (executive standard Q / SYC-104-2007) Of clay stabilizer Type I II III Appearance light yellow to reddish brown liquid, pale yellow viscous liquid colorless or light yellow solid Density (20 degrees C, g / cm³) 1 ~ 1.15 and 1 ~ 1.15 and 1.05 ~ 1.20 The value of pH (1%) 6 ~ 9 and 6 ~ 9 and 5 ~ 8 Solid content (%) > 10 > 45 > 85 Anti swelling rate (%) > 90 > 90 > 90 Use method three. ² according to the stratum clay content, using concentration is 0.25% ~ 0.50%. ² directly into the liquid, circulating evenly. Four, packaging, transportation and storage ² I and II type plastic bucket packaging, net weight (200 + 0.5) kg or (25 + 0.5) kg; type III (25 kg + 0.2) kg packaging bags. ² ventilation storage, to prevent exposure, since the production date storage period of 2 years

企业信息

河南省铭泰化工有限公司地处豫东北中原油田，位于山东与河南两省交界处，北临《水浒传》武松打虎之处 阳谷县，南临黄河，是当年刘邓大军南下度黄河之要道，贯通南北的京九铁路与在建的聊商高速为交通带来了便利。现拥有员工180余人，其中科技人员7名，管理人员11名，设驻外办事处5个，固定资产总投资2800万元。本公司设备先进，技术力量雄厚，主要产品有聚丙烯酰胺、聚丙烯酸钾、羧甲基纤维素钠、两性离子聚合物、乙烯基单体多元共聚物、广谱护壁剂，腐殖酸钾，抗高温抗盐增粘降失水剂，水解聚丙烯腈钾盐，铁铬木质素磺酸盐，植物胶，801随钻堵漏剂，单向压力封闭剂，阳离子聚丙烯酰胺，丙烯酰胺丙烯酸钠共聚物，低荧光防塌剂，磺化酚醛树脂、磺化沥青粉、磺化褐煤、无荧光防塌剂、防塌润滑剂、解卡剂，各种增粘剂，降粘剂，乳化剂，润滑剂，页岩抑制剂等各类化学剂，广泛应用于油田、采矿、造纸、纺织、污水处理等行业，年产值达3500万元，产品远销天津、江苏、安徽、陕西、内蒙古、新疆等地。质量就是生命，近20年来，公司始终坚持“以信誉为宗旨，以质量求发展”的经营理念，始终把质量放在第一位，高薪聘请研究生作为高科技技术攻关人员，积极组织参加各种技术交流活动，努力提高技术水平和产品质量，不断加强企业内部管理，坚持直接供货原则，确保向各用户供给合格产品。与各大油田长期保持着良好的供求业务往来关系。诚信为本，以信誉为宗旨，公司旨在通过真诚的合作与客户建立诚实守信的供求关系，充分利用现代化工具降低销售成本，缩减销售程序，给广大客户最优惠的价格，以高信誉赢得高回报。以创新求发展，以诚信赢市场，不断加大科技投入力度，扩大经营领域。“飞跃无限，诚达四海”，我公司始终坚持良好的企业形象和信誉，以一流的工作质量，竭诚为广大客户提供优质、高效的服务。 Henan MingTai chemical Co., LTD. Is located in northeast zhongyuan oilfield, and located in shandong province and henan provinces junction, north near the original novel wu3 song dozen tiger place - yanggu county, south near the Yellow River, is that year, liu DengDaJun south degrees north and south of the arteries and transfixion sideses jingjiu railway construction chat with high-speed traders convenient to have brought for traffic. Now has a staff of 180 people, including technical personnel 7, management personnel 11, set outside agency 5, fixed assets total investment 28,000, 000 yuan. The company equipment is advanced, technical force is abundant, the main products are PAM, polyacrylic acid potassium, sodium carboxy methyl cellulose, zwitterion polymers, vinyl monomer multivariate copolymer, broad-spectrum slurry-supported agent, humic acid potassium, high temperature resisting salt resistant viscosify drop water loss, hydrolyzed polyacrylonitrile potassium, iron chromium lignin sulfonates, plants, 801 glue the plugging agents with drilling, theunidirectional pressure agent, cationic polyacrylamide, acrylamide acrylic acid sodium copolymer, low fluorescence prevent collapse agent, phenolic resin, preparing sulphonated sulphonated lignite, asphalt powder, preparing sulphonated without fluorescence prevent collapse collapse agent, prevent sticking-releasing agent, lubricant, various viscous agent, drop adhesive, emulsifier, lubricant, shale of various chemical agents such as tilting preparations, widely used in oil field, mining, paper making, textile, sewage treatment and other industries, the annual production reaches 35 million yuan, products are exported to tianjin, jiangsu, anhui, shaanxi, Inner Mongolia, xinjiang, etc. Quality is life, nearly 20 years, the company always adhere to the "credibility for the purpose, to the quality strives for the development" business philosophy, always put quality first, well-paid graduate students as a high-tech technology research personnel, actively organize attend various technical exchanges, and strive to improve the technical level and product quality, continuously strengthening internal management, adhere to the principle of goods directly to each user to ensure supply of qualified products. And each big oilfield long-term keeps good relationship of supply and demand. The good faith for this, to the prestige for the purpose, the company aims to sincere cooperation