

# CHZ-120D型立式自动装盒机

产品名称	CHZ-120D型立式自动装盒机
公司名称	温州友联机械制造有限公司
价格	173000.00/台
规格参数	
公司地址	浙江省温州市瓯海娄桥创新路10号
联系电话	0755-84283425

## 产品详情

### CHZ-120D型立式自动装盒机

#### 产品特点：

CHZ-120D型立式自动装盒机是我公司结合国内外先进技术研发的新型机型，集光、电、气、机一体化的高科技产品。从而使设备性能和工作效率得到大幅度提高，实现快速装盒要求，且在快速运行时仍保持平稳、可靠状态。该机型适用于颗粒袋、软双铝、贴膏、创口贴、面膜贴、咖啡袋等类似袋状物品的自动加料及装盒。在线物料检测、说明书折叠（1-4折叠）与传送、说明书检测，纸盒吸取成形与传送、物料入盒、压印批号、纸盒两端纸舌封装（也可适用热熔胶）、缺料剔除及成品输出等全过程均属自动完成。1、PLC自动控制系统、变频调速，电气元件均采用国际知名品牌。2、采用人机界面操作系统。3、机械过载自动停机。4、自动剔除缺包装物和说明书的纸盒。5、故障显示、报警和成品计数。6、性能稳定、操作简便易懂。

#### 技术参数:

项目	参数
袋状加料数	1-12袋【视袋尺寸大小而定】
装盒速度	20-60盒/min【视纸盒大小而定】

纸盒	质量要求	250-350g/m <sup>2</sup>
	尺寸范围 (L×W×H)	(65-150) mm × (35-85) mm × (12-50) mm
说明书	质量要求	60-70g/m <sup>2</sup>
	未折叠尺寸范围 (L×W)	(80-250) mm × (90-170) mm
	折叠范围 (L×W)	【1-4】折
压缩空气	工作压力	0.6mpa
	耗气量	200-240/min
	电源	220V 50HZ
	主电机功率	1.10kw
	外形尺寸 (L×W×H)	2880mm × 1140mm × 1800mm
	整机净重	约1500kg

## Introduction :

This equipment is new model developing base on integrated domestic and foreign vanguard technology .It is high technology product incorporates pneumatic-photo-electro-mechanic which improve by a large on performance of equipment and working efficiency, realize encasing fast, keep running steady and reliable when fast running. This machine is suitable for sachet, pouch, soft al/al strips, wound plaster , ointment plaster, facial mask plaster, coffee bag into carton. On line product feeding and detecting, leaflet fold(1-4folds) and feeding, leaflet detecting, cant on opening and forming, products and leaflet pushing into carton, printing batch number, sealing carton with tuck-in or hot melt glue device. Automatically reject lacking of leaflet or product and finished product out.

- 1 International famous brand of electrical component such as PLC touch screen, frequency inverters, etc.
- 2 Adopt human-machine operation system.
- 3 Automatically stop when machine is overload.
- 4 Automatically reject lacking of package product and leaflet.
- 5 Automatically display trouble, Alarm and count finished products.
- 6 Stable performance, operation is easy.

## Technical parameter :

	Item	Parameters
	Bagging speed	1-12bag 【 Base on bag size 】
	Encasing speed	20-60 boxes/min 【 Base on carton size 】
Box	Quality requirement	250-350g/m <sup>2</sup>
	Dimension range ( L × W × H )	( 65-150 ) mm × ( 35-85 ) mm × ( 12-50 ) mm
Leaflet	Quality requirement	60-70g/m <sup>2</sup>

Unfolded leaflet specification ( L × W ) ( 80-250 ) mm × ( 90-170 ) mm

Fold range ( L × W ) 【1-4】 Fold

Compressed air Working pressure 0.6mpa

Air consumption 200-240/min

Power supply 220V 50HZ

Main motor power 1.10kw

Machine dimension ( L × W × H ) 2880mm × 1140mm × 1800mm

Machine weight 约1500kg