

CHZ-120G自动装盒机

产品名称	CHZ-120G自动装盒机
公司名称	温州友联机械制造有限公司
价格	178000.00/台
规格参数	
公司地址	浙江省温州市瓯海娄桥创新路10号
联系电话	0755-84283425

产品详情

CHZ-120G自动装盒机

产品特点：

CHZ-120G型立式自动装盒机是集光、电、气、机一体化的高科技产品。适用于软膏类药品（铝瓶及塑料瓶）及软包装类如避孕套自动包装盒。其工作过程为药板或物品的传送；药品说明书的传送（可进行1-4折的自动折叠）；纸盒自动成形与传送，将药板连带折好的说明书同时装入纸盒内；并完成自动打批号、两端纸舌封口等繁杂的封装过程（可加热溶胶机）。

- 1、PLC自动控制系统、变频调速，电器元件均采用国际知名品牌。
- 2、采用人机界面操作系统。
- 3、机械过载自动停机。
- 4、自动剔除缺包装物和说明书的纸盒。
- 5、故障显示、报警和成品计数。
- 6、性能稳定、操作简便易懂。

技术参数:

项目

参数

装盒速度

30-120盒/min

纸盒

质量要求

250-350g/m²【视纸盒大小而定】

尺寸范围 (L×W×H) (65-155) mm × (30-85) mm × (15-50) mm

说明书 质量要求 60-70g/m²

未折叠尺寸范围 (L×W) (80-250) mm × (90-170) mm

折叠范围 (L×W) 【1-4】折

压缩空气 工作压力 0.6mpa

耗气量 120-160L/min

电源 220V 50HZ

主电机功率 0.75kw

外形尺寸 (L×W×H) 2300mm × 1140mm × 1800mm

整机净重 约1200kg

CHZ-120G automatic Cartoning machine

Introduction :

CHZ-120G automatic Cartoning machine is set light, electricity, gas, machine integration of high-tech products. Apply ointment drugs (aluminum bottles and plastic bottle) and soft packaging such as automatic condom packing box. Its working process as the drug plate or the delivery of materials; drug instructions transmitted (1-4 can be folded automatic folding); automatic carton forming and transmitting, medicine plate joint folded leaflet at the same time into cartons; and complete the automatic batch number, paper tongues sealing both ends of the complex packaging process (SOL machine capable of heating). 1 International famous brand of electrical component such as PLC touch screen, frequency inverters, etc. 2 Adopt human-machine operation system.

3 Automatically stop when machine is overload.

4 Automatically reject lacking of package product and leaflet.

5 Automatically display trouble, Alarm and count finished products.

6 Stable performance,operation is easy.

Technical parameter :

	Item	Parameters
	Encasing speed	30-120 boxes/min
Box	Quality requirement	250-350g/m ² 【 Base on carton size 】
	Dimension range (L × W × H)	(65-155) mm × (30-85) mm × (15-50) mm
Leaflet	Quality requirement	60-70g/m ²
	Unfolded leaflet specification (L × W)	(80-250) mm × (90-170) mm

Fold range (L × W) 【1-4】 Fold

Compressed air Working pressure 0.6mpa

Air consumption 120-160L/min

Power supply 220V 50HZ

Main motor power 0.75kw

Machine dimension (L × W × H) 2300mm × 1140mm × 1800mm

Machine weight about1200kg