

CHZ-120I立式自动装盒机

产品名称	CHZ-120I立式自动装盒机
公司名称	温州友联机械制造有限公司
价格	178000.00/台
规格参数	
公司地址	浙江省温州市瓯海娄桥创新路10号
联系电话	0755-84283425

产品详情

CHZ-120I立式自动装盒机

产品特点：

CHZ-120I型立式自动装盒机是集光、电、气、机一体化的高科技产品。从而使设备性能和工作效率得到大幅度提高，实现快速装盒要求，且在快速运行时仍保持平稳、可靠状态。该机型适用多种规格（亦可装瓶亦可装铝塑版）物品的自动加料及装盒。自动上料机构调节方便、可在操作屏上任意设定需装盒的版数。在线物料输送、说明书折叠（1-4次折置）与传送、说明书检测、纸盒吸取成形与与传送、物料入盒、压印批号、纸盒两端纸舌封装（也可适用热熔胶）、缺料剔除及成品输出等全过程均属自动完成。

- 1、PLC自动控制系统、变频调速，电器元件均采用国际知名品牌。
- 2、采用人机界面操作系统。
- 3、机械过载自动停机。
- 4、自动剔除缺包装物和说明书的纸盒。
- 5、故障显示、报警和成品计数。
- 6、性能稳定、操作简便易懂。技术参数：

项目

参数

装盒速度

30-120盒/min

纸盒

质量要求

250-350g/m²【视纸盒大小而定】

尺寸范围 (L×W×H) (65-125) mm × (30-85) mm × (12-50) mm

说明书 质量要求 60-70g/m²

未折叠尺寸范围 (L×W) (80-250) mm × (90-170) mm

折叠尺寸范围 (L×W) 【1-4】折

压缩空气 工作压力 0.6mpa

耗气量 120-160L/min

电源 220V 50HZ

主电机功率 1.10kw

外形尺寸 (L×W×H) 2150mm × 1140mm × 1800mm

整机净重 约1100kg

Introduction :

This equipment is new model developing base on integrated domestic and foreign vanguard technology .It is high technology product incorporates pneumatic-photo-electro-mechanic which improve by a large on performance of equipment and working efficiency, realize encasing fast, keep running steady and reliable when fast running. This machine is suitable for automatic feeding product of multi-variety multi-specifications into carton (either for blister or bottle).Adjust automatic feeding structure conveniently,setup quantity of blisters on touch screen randomly.On line product feeding and detecting,leaflet fold(1-4folds) and feeding,leaflet detecting, carton opening and forming,products and leaflet pushing into carton,printing batch number,sealing carton with tuck-in or hot melt glue device. Automatically reject lacking of leaflet or product and finished product out.

- 1 International famous brand of electrical component such as PLC touch screen, frequency inverters, etc.
- 2 Adopt human-machine operation system.
- 3 Automatically stop when machine is overload.
- 4 Automatically reject lacking of package product and leaflet.
- 5 Automatically display trouble, Alarm and count finished products.
- 6 Stable performance,operation is easy.

Technical parameter :

	Item	Parameters
	Encasing speed	30-120 boxes/min
Box	Quality requirement	250-350g/m ² 【 Base on carton size 】
	Dimension range (L × W × H)	(65-125) mm × (30-85) mm × (12-50) mm
Leaflet	Quality requirement	60-70g/m ²

Unfolded leaflet specification (L × W) (80-250) mm × (90-170) mm

Fold range (L × W) 【 1-4 】 Fold

Compressed air Working pressure 0.6mpa

Air consumption 120-160L/min

Power supply 220V 50HZ

Main motor power 1.10kw

Machine dimension(L × W × H) 2150mm × 1140mm × 1800mm

Machine weight about 1100kg