

# 进口杜笙氟化物去除离子交换树脂

产品名称	进口杜笙氟化物去除离子交换树脂
公司名称	北京华豫清源国际贸易有限公司
价格	.00/升
规格参数	
公司地址	北京市丰台区花乡造甲村南里1号楼105室
联系电话	86-01052456750 13269232873

## 产品详情

杜笙tulsion® ch-87

iso-9001/iso-14001/ohsas-18000

氟化物选择吸附树脂

tulsion® ch-87 是一款去除水溶液中氟离子的专用的凝胶型选择性离子交换树脂。它是具有氟化物选择性官能团的交联聚苯乙烯共聚物架构的树脂。

tulsion® ch-87 的去除氟离子的能力可以达到1ppm以下的水平。它在中性至碱性的ph范围内有极高的工作效率，并且很容易再生。

典型特性 ( typical characteristics ) : tulsion® ch-87

主体结构/matrix structure 聚苯乙烯共聚物/polystyrene copolymer

物理型式/physical form 湿润球状/moist spherical beads

官能团/functional group 氟选择性官能基/fluoride selective

目数/screen size uss (湿) 16 to 50

粒度/particle size(95% minm.) 0.3 - 1.2 mm

湿度/moisture content  $45 \pm 3\%$

反洗稳定密度/backwash settled density 830 - 860 gm/lit(52 - 54 lbs/cft)

最大温度/maximum thermal stability 60 ( 140 )

ph范围/ph range 7 - 11

测试 ( testing ) : tulsion® ch-87

离子交换树脂的抽样和测试是按标准的测试程序，即astmd - 2187和is - 7330，1998.

包装 ( packing ) : tulsion® ch-87

super sack

1000 lit

super sack

ms drums

180 lit.

ms drums

hdpe lines bags

25 lit.

hdpe lines bags

for handling, safety and storage requirements please refer to the individual material safety data sheets available at our offices. the data included herein are based on test information obtained by thermax limited. these data are believed to be reliable, but do not imply any warranty or performance guarantee. tolerances for characteristics are per bis/astm. we recommend that the user should determine the performance of the product by testing on his own processing equipment.

for further information, please contact: :