

T502 混合型液体屏蔽酚

产品名称	T502 混合型液体屏蔽酚
公司名称	辽宁天合精细化工股份有限公司
价格	.00/个
规格参数	型号:T502 品牌:天合品牌 产品规格:180kg/桶
公司地址	锦州市太和区解放西路100号
联系电话	86-416-5160515 15084168570

产品详情

型号	T502	品牌	天合品牌
产品规格	180kg/桶	执行标准	国标行标企标

产品简介

t502是采用苯酚和异丁烯为原料制得的油品添加剂，在油中起抗氧化和防胶作用。该产品油溶性好，。

产品特点

产品组成：2,6-二叔丁基苯酚含量>75%其它组分为同类屏蔽酚抗氧化剂 抗氧化性及防胶性优良 油溶性好：常温下为液体

用途

用于燃料油用于调制工业润滑油，如汽轮机油、变压器油、液压油、机床用油等橡胶中作防老剂参考0%

技术参数

项目	典型数据
密度(20oc) , (gb/t1884) , kg/m3	930

闪点(开口) , (gb/t3536) , oc 96

运动粘度(40oc) , (gb/t265) , mm2/s 8.0

本产品执行企业标准q/jth002-2007
包装及处置

用200升金属桶包装 , 储存于干燥、清洁、通风库房中。安全注意事项参见相关的化学品安全技术说

=====
=====

description 502 is a lubricant additive component prepared from phenol and isobutylene. it provides oils with excellent antioxidation and antigum performance. this product is a liquid at normal temperature, and readily soluble in oils.

special features product composition: 2, 6-di-tert-butyl phenol, >75%. others are similar hindered phenol antioxidants fine antioxidation and antigum performance good oil solubility liquid at normal temperature, with fine flowability

applications used for fuel oils used for blending industrial lubricating oils such as turbine oils, transformer oils, hydraulic oils and machine-tool oils, etc used as anti-aging agent in rubber the dosage: 0.1-1.0%

characteristics

item	typical value
density (20oc), (astm d1298), kg/m3	930
flash point (pmcc), (astm d93), oc	96
kinematic viscosity (40oc), (astm d445), mm2/s	8.0

the enterprise standard q/jth002-2007

points for attention it is packed in metal drums of 200 litres. store in dry, clean and well ventilated warehouses. for the details of health and safety precautions, please see the related material safety data sheet.