

PPS日本宝理阻燃级玻纤增强高机械强度

产品名称	PPS日本宝理阻燃级玻纤增强高机械强度
公司名称	京冀（广州）新材料有限公司
价格	34.00/件
规格参数	PPS:玻纤增强30% 超高流动性:高机械强度 日本宝理:阻燃级
公司地址	广州市南沙区丰泽东路106号（自编1号楼）X130 1-E014087（注册地址）
联系电话	18938547875 18938547875

产品详情

????:

1????????????????????

2???????ABS?PC??100-

150????????????????????

????????????????PPS??PPS????????????????????????????

(1)?????:PPS????????45%??

?;??

(2)?????:??

???

(3)?????:????????????????

(4)??/??:????????????

Molding Properties: 1, amorphous material, hygroscopic small, but should be dry after molding. 2. The fluidity is between ABS and PC, it solidifies quickly, shrinks little, decomposes easily, chooses the higher injection pressure and the injection speed. Take the mold temperature 100-150 degrees. Main runner taper should be large, runner should be short. The scope of application can be generally used in the manufacture of PPS pipe, PPS plate and other materials,

mostly used in construction, home. (1) automobile industry: PPS is used in about 45% of the automobile industry, mainly for automotive functional parts, igniters, heaters, thermostats, lamp holders, bearings, such as the replacement of metal exhaust cylinder cycle valve and pump impeller, pneumatic signal demodulator, etc. . (2) machinery industry: for Shell, structure, wear-resisting parts and sealing materials, specifically pump body, valve, bearing, bearing bracket, piston ring and gear, etc. . (3) textile fiber: for special industrial dust removal equipment. (4) film/insulating paper: Used for motor insulation.