

# ASB-XE-175 氙灯

产品名称	ASB-XE-175 氙灯
公司名称	长春博盛量子科技有限公司
价格	面议
规格参数	
公司地址	吉林省长春市高新开发区硅谷大街1198号
联系电话	86-043185916189

## 产品详情

[光电测量产品 >>](#) [光源 >>](#) ASB-XE-175 氙灯

Feature & #118alve Lamp.	Type: CERMAX® LX175F Power: 200 Watts (maximum) Power Range: 150-200 W Color Temperature: 5600 ° K Current: 14 amps DC (nominal) Average Life: Typically 1000 hours (500 hours minimum) Voltage: 12-17V (14V nominal) Trigger Voltage: 25 Kilovolts Boost Voltage: 140-200 Volts Current Leakage: < 300mA  ASB-XE-175-EX: UV extended, 200nm ~ 2200nm (dominant, 250nm ~ 1100nm) ASB-XE-175-BF: Ozone blocking, 320nm ~ 700nm ASB-XE-175-BFEX: NIR extended, Ozone blocking, 320nm ~ 2200nm (dominant, 320nm ~ 1100nm)
Weight:	7.5 lbs. (3.4 kg)
Input Line:	95-136 VAC, 50/60 Hz (only)
Input Current:	3.5 amp.
Environment:	Operating: +6 to +45 ° C Storage: -40 to +70 ° C
Front Panel:	Brightness Control (0-100%) Output Aperture
Side Panel:	Main Power (On/Off) Line Cord Jack (IEC 320) (US to IEC Line Cord included) Fuse Holder - MDL-5

Caution:

Damage to glass or fused silica fiber optic lightguides can occur due to high temperatures associated with Xenon lamps. Use our liquid light guides (order separately).