

LED车铝天花灯筒灯射灯室明照明标杆产品

产品名称	LED车铝天花灯筒灯射灯室明照明标杆产品
公司名称	中山市永誉照明灯具有限公司
价格	15.00/个
规格参数	
公司地址	广东省中山市横栏镇永兴工业区良晖工业园2栋5楼
联系电话	86-076087551513/87663388 13923359584

产品详情

车铝天花灯技术参数

一、材质：选用优质高纯度铝材制作而成。使用先进的阳极氧化处理技术，使灯具更加美观耐用。

二、结构：结构简洁、明了，安装简易方便，性价比高。

三、节能降耗：在相同亮度情况下，LED节能灯1000小时仅耗1度电，普通白炽灯17小时耗1度电，普通节能灯100小时耗1度电。

四、超长寿命：LED超级节能灯的使用理论寿命可达上万小时以上，普通白炽灯使用寿命1000多小时。

五、保护视力：光线中不含紫外线和红外线，无辐射，无污染。普通节能灯管和白炽灯光线中含有紫外线和红外线，长期照射对人体有害。

六、环保无毒：不含汞和铅等有害物质，无辐射，无电磁干扰，而且不会产生电磁干扰，普通灯管中含有汞和铅等有害物质，对人体有害。

七、保护视力：采用直流电源驱动，无频闪，普通灯都是交流驱动，就必然产生频闪对长时间眼睛不利。

八、节能环保：节能降耗，节能环保，普通白炽灯仅有20%电能转化为可见光，另80%电能转化为热能，对有限的资源是极大的浪费。

九、安全系数高：所需电压、电流较小，发热少，无安全隐患。

LED ceiling light is a new type of lighting fixture that is widely used in homes, offices, and commercial spaces. It is known for its energy efficiency, long lifespan, and low heat output. The light is produced by a series of small LED chips that are mounted on a metal or plastic housing. The housing is designed to dissipate heat and protect the chips from dust and moisture. The light is controlled by a driver circuit that converts AC power to DC power. The driver circuit also provides current regulation and protection for the LED chips. The light is available in various colors and brightness levels. It is a popular choice for modern lighting design.

LED ceiling light

LED ceiling light is a new type of lighting fixture that is widely used in homes, offices, and commercial spaces. It is known for its energy efficiency, long lifespan, and low heat output. The light is produced by a series of small LED chips that are mounted on a metal or plastic housing. The housing is designed to dissipate heat and protect the chips from dust and moisture. The light is controlled by a driver circuit that converts AC power to DC power. The driver circuit also provides current regulation and protection for the LED chips. The light is available in various colors and brightness levels. It is a popular choice for modern lighting design.

十一、天花灯技术参数：

型号	功率	LED	LED-YY-THD
尺寸	95MM	AC85-240V	频率(50Hz)
LED	90-106lm/W	90-106lm/W	90-106lm/W
投光距离	≥3.7米	红：620-625nm、绿白520-502-8700K、蓝青475-490nm	白：5500-6000K、暖白：5000K
		车铝-7系合金	

十二、适用实例: