

# 沈阳西门子中国代理商CPU供应

产品名称	沈阳西门子中国代理商CPU供应
公司名称	浔之漫智控技术（上海）有限公司总部
价格	3400.00/件
规格参数	品牌:西门子 货期:现货 产地:德国
公司地址	上海市松江区石湖荡镇塔汇路755弄29号1幢一层A区213室
联系电话	15021292620 15021292620

## 产品详情

沈阳西门子中国代理商CPU供应

Switch ES Power 软件

Switch ES Power 是用于具有通讯能力的 SENTROM 断路器的共享软件平台。其具有的优点是，所有具体设备的设置项在外观和处理方面都是相同的。

Switch ES Power 可以用于通过 PROFIBUS DP 配置、记录、操作和监视 SENTRON 3WL 和 SENTRON 3VL 断路器。

您可在以下网址获取详细信息：

<http://www.siemens.de/sentron>

优势Switch ES Power 软件

在一个软件中实现参数化、记录、运行和监视

对测量值和设置进行记录

清晰显示所有可用参数

所有可用的状态信息和测得值都清晰的显示在对话框中

对 SENTRON 3WL 和 SENTRON 3VL 使用一个软件

通过非周期的 PROFIBUS DP-V1 数据通信简单的连接构建

使用 Breaker Data Adapter (BDA) 软件对参数实现了相同的存储格式

简单易用的 Windows 接口

操作无需编程知识

Switch ES Power 的对象管理器

用于断路器参数的统一数据管理

如果更换了组件，实现自动参数化

设计 Switch ES Power

The design of both the data tree and the individual data windows has been cross-referenced and harmonized with the structure of the Breaker Data Adapter. As a result, the same functions and information are available. Due to its support of the innovative PROFIBUS DPV1 function, it is particularly easy to link up a computer to the PROFIBUS using Switch ES Power. Simply connect, select the PROFIBUS address and start communications, even if the SENTRON circuit-breakers are simultaneously exchanging data with another station (e.g. S7) via the PROFIBUS.

With Switch ES Power, it is also possible to create parameter sets offline without a direct connection to the circuit-breaker. These parameter sets can then be transmitted to the SENTRON circuit-breakers in the plant at a later stage.

功能

Switch ES Power 的在线功能

Switch ES Power 用于装载和显示控制识别数据。根据断路器配置，可以显示保护功能（LSIGN）的参数、扩展保护功能、可配置门限值、通讯和可配置输出模块。这些设置都可以相应的进行修改、装载和保存在开关设备上。根据断路器类型，可以使用丰富的在线对话框。

主视图

诊断窗口

测量值窗口

显示谐波分析的窗口

显示曲线形式存储器的窗口

## 用于维护和统计的对话框

BDA 和 Switch ES Power 的存储格式是相同的，这就是说，例如可以使用 Switch ES Power 生成核心参数文件，然后将其复制到带有 BDA 软件的笔记本电脑上，供维护人员使用。

Switch ES Power 支持所有用于西门子 PC/笔记本的 PROFIBUS 卡  
有些卡需要安装附加软件包（驱动程序）；如需了解详情，请参考目录 CA 01。

## 集成 Switch ES Power 的对象管理器

Switch ES Power 的对象管理器（OM）用于将 Switch ES Power 集成到 STEP 7 环境中，也就是集成到全集成自动化（TIA）环境中。这使 Switch ES Power 能够从 STEP 7 的 HWConfig Tool 中进行调用，对 SENTRON 3WL/3VL 断路器进行配置。而数据会存储在 STEP 7 数据库中，并在 PROFIBUS DP 启动（SPS，从站）期间自动传输给设备。

## 使用 Switch ES Power 设置参数组 A

沈阳西门子中国代理商CPU供应

沈阳西门子中国代理商CPU供应