

武汉西门子授权一级代理商电源供应商

产品名称	武汉西门子授权一级代理商电源供应商
公司名称	浔之漫智控技术（上海）有限公司总部
价格	5600.00/件
规格参数	品牌:西门子 货期:现货 产地:德国
公司地址	上海市松江区石湖荡镇塔汇路755弄29号1幢一层A区213室
联系电话	15021292620 15021292620

产品详情

武汉西门子授权一级代理商电源供应商The SIDOOR NT40 switched-mode power supply unit is operated with 230 V AC ($\pm 15\%$), 50/60 Hz, to power the elevator door controllers. It is especially suitable for door systems with high door weights. On the output side, the power supply unit delivers a voltage of 36 V DC ($\pm 3\%$) SELV at a rated output power of < 100 W. In order to enable fast acceleration/deceleration of the doors by the controller, the device can briefly (< 2 s) deliver a current of 15 A (corresponds to a short-time power output of 540 W). 技术规范 Article number 6FB1112-0AT20-3PS0SIDOOR NT40 Installation type/mounting Mounting type Four 5 mm screws Supply voltage Rated value (AC) 230 V relative symmetrical tolerance of the supply voltage 15 % Line frequency permissible range, lower limit 50 Hz permissible range, upper limit 60 Hz Input current Current consumption for 2 s, max. 3.5 A Rated value at 230 V AC 0.7 A Operational current of fuse protection at input, min. 6 A Operational current of fuse protection at input, max. 10 A Tripping characteristic class of fuse protection at input B Output voltage Rated value (DC) 36 V; SELV Relative symmetrical tolerance of the output voltage 3 % Output current Current output (rated value) 2.5 A Temporary overload current (for 2 s maximum) 15 A Power Active power input, max. 100 W Emitted active power, max. Emitted active power (restricted to 2 s) 540 W Efficiency at 230 V AC (with 100 W emitted active power) 90 % Active apparent power, max. 650 V · A Standards, approvals, certificates CE mark Yes EAC (formerly Gost-R) TV Inspectorate approval China RoHS compliance Standard for EMC EMC Directive 2004/108/EC, EN 12015, EN 12016 Standard for safety EN 61010-1 / EN 61010-2-201 Ambient conditions Ambient temperature during operation min. $-20\text{ }^{\circ}\text{C}$ max. $55\text{ }^{\circ}\text{C}$ Remark No direct exposure to the sun Ambient temperature during storage/transportation Storage, min. Storage, max. $70\text{ }^{\circ}\text{C}$ Transportation, min. $-40\text{ }^{\circ}\text{C}$ Transportation, max. Altitude during operation relating to sea level Installation altitude above sea level, max. 2 000 m Relative humidity No condensation, min. 10 % No condensation, max. 93 % Cables Cable length Input side 2 m Output side 1.5 m Connection method Design of electrical connection at input SCHUKO connector DIN 49.441, CEE7/VIIDimensions Width 270 mm Height 55 mm Depth 80 mm 品牌产品名称规格型号 SIEMENS 模块 6ES7131-6BH01-0BA0 SIEMENS 接头 6GK1901-1BB10-2AA0 SIEMENS 触摸屏 6AV6648-0CC11-3AX0 SIEMENS 触摸屏 6AV6648-0CE11-3AX0 SIEMENS 模块 6ES7142-3BH00-0XA0 SIEMENS 模块 6ES7288-3AE08-0AA0 SIEMENS 模块 6ES7288-3AR04-0AA0 SIEMENS 模块 6ES7288-5CM01-0A

A0SIEMENS触摸屏6AV2123-2MB03-0AX0SIEMENS电缆6XV1840-2AH10SIEMENS触摸屏6AV2123-2GB03-0AX0SIEMENS底座6ES7193-6BP00-0BA0SIEMENS底座6ES7193-6BP00-0DA0SIEMENS模块6ES7288-3AQ02-0AA0SIEMENS模块6ES7141-3BH00-0XA0SIEMENS模块6ES7288-3AE04-0AA0SIEMENS模块6ES7288-2DE08-0AA0SIEMENS模块6ES7288-3AM03-0AA0SIEMENS内存卡6ES7954-8LE03-0AA0SIEMENS模块6ES7521-1BH10-0AA0SIEMENS模块6ES7134-6GF00-0AA1SIEMENS模块6ES7288-3AM06-0AA0SIEMENS模块6ES7241-1CH32-0XB0SIEMENS触摸屏6AV2124-0MC01-0AX0SIEMENS模块6ES7288-2DR32-0AA0Siemens模块6ES7288-2DR08-0AA0Siemens电池板6ES7288-5BA01-0AA0Siemens交换机6GK5004-1BD00-1AB2SIEMENS电源6ES7288-0CD10-0AA0Siemens模块6ES7288-3AR02-0AA0SIEMENS模块6ES7511-1AK02-0AB0SIEMENS模块6ES7132-6BF01-0AA0SIEMENS存储卡6ES7954-8LL03-0AA0Siemens模块6ES7194-3AA00-0BA0Siemens模块6ES7288-1CR60-0AA0SIEMENS存储卡6ES7954-8LC03-0AA0Siemens交换机6GK5116-0BA00-2AC2Siemens存储卡6ES7954-8LF03-0AA0SIEMENS模块6ES7511-1CK01-0AB0Siemens电源6EP1961-3BA21Siemens交换机6GK5201-3JR00-2BA6SiemensCPU模块6ES7416-3FS06-0AB0SiemensWINCC软件6AV6381-2BE07-5AV0SiemensWINCC软件6AV6381-2BH07-5AV0SiemensWINCC软件6AV6381-2BF07-5AV0SiemensWINCC软件6AV6381-2BM07-5AV0SiemensWINCC软件6AV6381-2BN07-5AV0SiemensWINCC软件6AV6381-2BS07-5AV0SiemensWINCC软件6AV6381-2BQ07-5AV0SIEMENS交换机6GK5108-0BA00-2AC2Siemens伺服轴卡6SN1118-0DM31-0AA1SIEMENS交换机6GK5216-4BS00-2AC2Siemens轴卡6SN1118-0DM31-0AA2Siemens驱动6SN1118-0AD11-0AA0Siemens变频器6SE6440-2UD31-5DA1Siemens电源6EP3437-8SB00-0AY0Siemens模块6ES7516-3AN02-0AB0SIEMENS基座6ES7193-6BP20-0BA0Siemens软件6AV2101-0AA05-0AA5Siemens软件6AV6371-1DV07-5AX0SIEMENS变频器6SE6420-2AB12-5AA1SIEMENS多功能表7KM3220-0BA01-1DA0SIEMENS模块6ES7288-1ST40-0AA1SIEMENS模块6ES7288-1SR30-0AA1SIEMENS模块6ES7288-1SR60-0AA1SIEMENS模块6ES7288-1SR20-0AA1Siemens模块6ES7288-1ST30-0AA1SIEMENS模块6ES7288-1SR40-0AA1SIEMENS模块6ES7288-1ST20-0AA1SIEMENS模块6ES7288-1ST60-0AA1SIEMENS电缆6XV1861-4AU10Siemens内存卡6ES7954-8LP03-0AA0Siemens电源6EP4136-3AB00-0AY0武汉西门子授权一级代理商电源供应商