

武汉西门子授权代理商变频器供应商

产品名称	武汉西门子授权代理商变频器供应商
公司名称	浔之漫智控技术（上海）有限公司总部
价格	5200.00/件
规格参数	品牌:西门子 货期:现货 产地:德国
公司地址	上海市松江区石湖荡镇塔汇路755弄29号1幢一层A区213室
联系电话	15021292620 15021292620

产品详情

武汉西门子授权代理商变频器供应商

湖北西门子电缆代理商，武汉西门子通讯电缆代理商，济南西门子模块代理商。西门子授权一级代理商，深圳西门子授权总代理商，浔之漫智控技术（上海）有限公司，欢迎致电浔之漫智控技术上海有限公司采购

自然人独资。经营范围：

从事自动化科技、机电领域内的技术开发、技术转让、技术咨询、技术服务、工业自动化设备安装、工业自动化控制设备、

电气设备、机电设备、电子产品、五金产品、金属材料、仪器仪表、橡塑制品销售、商务信息咨询、软件开发、建筑装修装饰建设工程施工、

建筑安装工程（除特种设备），机械设备租赁（不得从事金融租赁），物业管理。工业自动化设备加工、销售。

浔之漫智控技术上海有限公司在经营活动中精益求精，具备如下业务优势：SIEMENS 可编程控制器

1、SIMATIC S7 系列PLC：S7-200、S7-1200、S7-300、S7-400、ET-200

2、逻辑控制模块 LOGO！230RC、230RCO、230RCL、24RC、24RCL等

3、SITOP直流电源 24V DC 1.3A、2.5A、3A、5A、10A、20A、40A可并联.

4、HMI 触摸屏TD200 TD400C K-TP

SIDOOR geared motors are a combination of gear unit, motor and sensor. They are easy to connect to the controller via the interface provided and are automatically detected during commissioning.

The maintenance-free, variable speed drive unit comprises a DC motor with non-self-locking gearing.

The geared motors must be selected according to the mass to be moved. Two different versions are available for each of the SIDOOR M2 to SIDOOR M5 geared motors, with gear output on the left or on the right: The gear outlet direction is defined as left or right when viewing the gear unit from the front.

SIDOOR M2 geared motors (max. door weight 120 kg)

SIDOOR M2 L (pinion left) 6FB11030AT105MA0

SIDOOR M2 R (pinion right) 6FB11030AT115MA0

SIDOOR M3 geared motors (max. door weight 180 kg)

SIDOOR M3 L (pinion left) 6FB11030AT104MB0

SIDOOR M3 R (pinion right) 6FB11030AT114MB0

SIDOOR M4 geared motors (max. door weight 400 kg)

SIDOOR M4 L (pinion left) 6FB11030AT103MC0

SIDOOR M4 R (pinion right) 6FB11030AT113MC0

SIDOOR M5 geared motors (max. door weight 600 kg)

SIDOOR M5 L (pinion left) 6FB11030AT103MD0

SIDOOR M5 R (pinion right) 6FB11030AT113MD0

Geared motors: SIDOOR M2 L 6FB11030AT105MA0 (version with pinion left), SIDOOR M3 L 6FB11030AT104MB0 (version with pinion left), SIDOOR M4 L 6FB11030AT103MC0 (version with pinion left), SIDOOR M5 L 6FB11030AT103MD0 (version with pinion left) (Images are shown in the order from bottom to top)

技术规范

Article number

6FB1103-0AT10-5MA0

6FB1103-0AT11-5MA0

6FB1103-0AT10-4MB0

6FB1103-0AT11-4MB0

6FB1103-0AT10-3MC0

6FB1103-0AT11-3MC0

6FB1103-0AT10-3MD0

6FB1103-0AT11-3MD0

SIDOOR M2 L

SIDOOR M2 R

SIDOOR M3 L

SIDOOR M3 R

SIDOOR M4 L

SIDOOR M4 R

SIDOOR M5 L

SIDOOR M5 R

Supply voltage

Rated value (DC)

24 V

30 V

Input current

Operational current (rated value)

1.8 A

4 A

7.5 A

Power

Active power input

43 W

120 W

225 W

Mechanical data

Torque of the rotary operating mechanism (rated value)

1.05 N · m

3 N · m

6.8 N · m

Speed, max.

0.5 m/s

0.65 m/s

0.75 m/s

Gear ratio

15

Number of pulses per revolution, max.

100

Weight of door, max.

120 kg

180 kg

400 kg

600 kg

Standards, approvals, certificates

CE mark

Yes

UL approval

No

Yes

EAC (formerly Gost-R)

TV Inspectorate approval

China RoHS compliance

Ambient conditions

Ambient temperature during operation

min.

-20 ° C

max.

50 ° C

Ambient temperature during storage/transportation

Storage, min.

-40 ° C

Storage, max.

85 ° C

Dimensions

Height of motor

90 mm

98 mm

115 mm

124 mm

Length of motor

207 mm

236 mm

275 mm

344 mm

Diameter of motor

48 mm

63 mm

80 mm

Width of gear unit, including drive pinion

85 mm

105 mm

111 mm

附件

The following accessories are available for the SIDOOR M2 to SIDOOR M5 geared motors:

Rubber-metal anti-vibration mount for low-noise door operation

6FB11040AT020AD0 for SIDOOR M2 and SIDOOR M3 geared motors (door weights up to 180 kg)

6FB11040AT010AD0 for SIDOOR M4 and SIDOOR M5 geared motors (door weights up to 600 kg)

Mounting bracket 6FB11040AT010AS0 for the geared motor mount for flexible accommodation of the rubber-bonded metal

See "Accessories" .