

# 煤矿用阻燃控制电缆 矿用电缆 矿用电缆型号

产品名称	煤矿用阻燃控制电缆 矿用电缆 矿用电缆型号
公司名称	扬州市红旗电缆有限公司
价格	面议
规格参数	
公司地址	扬州高邮菱塘工业园
联系电话	86-015952501233 15862870408

## 产品详情

矿用电缆 煤矿用移动类阻燃橡胶套软电缆

Mobile fire retardant rubber soft cables for mines

矿用电缆 煤矿用移动类阻燃橡胶套软电缆

执行标准 Standards implemented: MT 818-1999

产品用途:产品供煤矿移动电器设备及采掘机械配套用。

矿用电缆 : 煤矿用移动类阻燃橡胶套软电缆型号名称 Model descriptions

型号 Model	名称 Descriptions
MY	煤矿用移动橡胶套软电缆 Mobile rubber soft cables for mines
MYQ	煤矿用移动轻型橡胶套软电缆 Mobile light type rubber soft cables for mines
	煤矿用移动屏蔽橡胶套软电缆 Mobile shielded rubber soft cables for mines

MYP	
MC	采煤机橡胶套软电缆 Rubber soft cables for coal cutter in mines
MCP	采煤机屏蔽橡胶套软电缆 Shielded rubber soft cables for coal cutter in mines
MZ	煤矿用电钻橡胶套电缆 Electric drill rubber cables for mines
MZP	煤矿用电钻屏蔽橡胶套电缆 Electric drill shielded rubber cables for mines

矿用电缆：煤矿用移动类阻燃橡胶套软电缆使用特性

Service characteristics

型号 Model	MYQ MZ MZP MY MYP
额定电压 U0/U Rated voltage	0.3/0.5kv 0.38/0.66kv 0.6/1.14kv
电缆长期允许工作温度 Long-term service temperature of the cable conductor	65
电缆的最小弯曲半径 Minimun bending radius	6D

电缆规格 Specifications

型号 Model	芯数 Core number	额定电压 KV Rated voltage	标称截面mm <sup>2</sup> Nominal sectional		
			动力线芯 Core for power	地线芯 Core for ground	控制线芯 Pilot
MY	1	0.38/0.66	50-150	-	-
	3+1		3x4-3x70	1x4-1x25	-
MZ MZP	3+1、3+1+1	0.3/0.5	3X2.5-3X4	1X2.5-1X4	1X2.5-1X4
MYQ	2、3、4、7、12	0.3/0.5	1.0-2.5	-	-
	3+1		3X1.0-3X2.5	1X0.75-1X1.5	-
MC	3+1+3	0.38/0.66	3x16-3x50	1x4-1x10	3x2.5-3x4
MCP	3+1+3	0.38/0.66	3x16-3x50	1x4-1x10	3x2.5-3x4
		0.66/1.14	3x35-3x95	1x6-1x25	
MYP	3+1	0.38/0.66	3x4-3x70	1x4-1x25	-
		0.66/1.14	3x10-3x95	1x10-1x25	-

电缆主要技术性能

Major technical performances

1、 电缆导体直流电阻

DC resistance of the conductor

型号 Model	厂用电缆 标称截面 Nominal sectional (mm <sup>2</sup> )	煤矿用移动类阻燃橡套软电缆 200C时导体直流电阻( /Km) DC resistance of the conductor at 20		型号 Model	
		不镀锡 Untinned	镀锡 Tinned	不镀锡 Untinned	镀锡
MYQ	1.0	19.5	20.0	MY MYP	1
	1.5	13.3	13.7		1
	2.5	7.98	8.21		2
MZ MZP	2.5	-	8.82		3
	4	-	5.39		5
MC MCP	4	-	5.09		7
	6	-	3.39		9
	10	-	1.95		1
	16	-	1.24		1
	25	-	0.795		1
	35	-	0.565	2	
	50	-	0.393	3	
MY MYP	4	4.95	5.09	4	
	6	3.30	3.39		

2、矿用电缆：煤矿用移动类阻燃橡套软电缆 电缆的绝缘电阻 Dielectric resistance

型号 Model	动力线芯标称截面mm <sup>2</sup> Core for power nominal sectional	20 时绝缘电阻 ( M Km) Dielectric resistance at 20	型号 Model	动力线芯标称截面mm <sup>2</sup> Core for power nominal sectional	20 时绝缘 (Km) Dielect 2
MYQ	1.0	160	MY MYP	10	
	1.5	160		16	
	2.5	160		25	
MZ MZP	2.5	160		35	
	4	160		50	
MC MCP	16	120		70	
	25	120		95	
	35	100		120	
	50	100		150	
	70	80		185	
	95	80		240	
	限制线芯Control core	100		300	
	MY MYP	4		200	400
	6	180		-	

3、电缆其它主要技术性能 Other major technical performances

(型号 Model:MY MYP MYQ MC MCP MZ MZP)

序号 Serial number	项目 Items	技术性能
1	线芯直流电阻( /Km) Core DC resistance	见

2	绝缘电阻( M Km) Insulating resistance		见
3	5min工频电压试验 5min power frequency voltage experiment	0.66/1.14	3.7KV工频电压绝缘不击穿 3.7KV power frequency voltage insulation
		0.38/0.66	3KV工频电压绝缘不击穿 3KV power frequency voltage insulation
		0.3/0.5	2KV工频电压绝缘不击穿 2KV power frequency voltage insulation
		控制线芯Control core	1.5KV工频电压绝缘不击穿 1.5KV power frequency voltage insulation
4	热延伸试验 The heat extends the experiment	175%	
5	单根垂直燃烧试验 Single wire burning test	MT386	
6	成束燃烧试验 Group burning test	最大线芯截面积在50mm <sup>2</sup> 及以上时 符合A类成束燃烧试验要求 M area more than 50mm <sup>2</sup> conforms A kind group burning	
7		最大线芯截面积在50mm <sup>2</sup> 及以下时 符合B类成束燃烧试验要求 M area more than 50mm <sup>2</sup> conforms B kind group burning	

扬州红旗电缆制造有限公司集电线电缆科研、生产与销售为一体的专业性公司。公司严格按国内的GB、JB、GJB、MT标准及国际电工委员会的IEC60189、IEC60227、IEC60502、IEC60584、IEC60092、IEC60331、IEC60332、IEC61034标准及国外先进的JCS258B、BS5308、VDE0266、NES713、OCT12100标准以及企标组织生产的各类产品有：船用电缆、矿用通信电缆、电器装备电缆、矿用电线、舰船用电线等。公司一直坚持以"科技铸就品牌、精益求精提升品质，至尊至诚服务客户"的发展宗旨，不断遵循"追求卓越、严格务实、规范守信"的企业精神，积极为广大客户提供最优质的服务，相互促进共同发展。如您对本款产品矿用电线：煤矿用移动类阻燃橡套软电缆有什么疑问，欢迎来电。联系人：吴连飞  
联系电话：15862870408 传真：0514-84232111 邮箱：1692601928@qq.com