

金属电缆防水接头 防爆螺旋式电缆接头 金属固定头 铜合金镀镍

产品名称	金属电缆防水接头 防爆螺旋式电缆接头 金属固定头 铜合金镀镍
公司名称	杭州赛格机电设备有限公司
价格	2.00/只
规格参数	
公司地址	杭州市德胜中路388号（长城机电2133柜）
联系电话	086-57185357333 13777424899

产品详情

产品简介

金属铜镀镍，防水等级IP68，可接受定制环保材质和非常规尺寸。工作温度-40 ~ +100 短时可达 +120，拥有SGS，IP68，CE等认证

规格	产品型号	螺纹外径AG	电缆范围	螺纹长度GL	扳手径	螺纹间距
M8*1	M8B-06	8	2-6	6	10	1
M8*1	M8BS-04		1-4	6	10	1
M10*1	M10-06	10	2-6	6	10	1
M12*1.5	M12B-06	12	3-7	6	14	1.5
M12*1.5	M12B-08		3-8	6	16	1.5

M14*1.5	M14B-06	14	3-7	6	16	1.5	1
M14*1.5	M14B-08		3-8	6	18	1.5	1
M16*1.5	M16B-08	16	4-8	7	18	1.5	1
M16*1.5	M16B-10		6-10	7	20	1.5	1
M18*1.5	M18B-10	18	6-10	7	20	1.5	1
M20*1.5	M20B-10	20	6-10	7	22	1.5	5
M20*1.5	M20B-12		8-12	8	22	1.5	5
M20*1.5	M20B-14		10-14	7	24	1.5	5
M22*1.5	M22B-12	22	8-12	8	24	1.5	5
M22*1.5	M22B-14		10-14	8	24	1.5	5
M24*1.5	M24B-14	24	10-14	8	27	1.5	5
M25*1.5	M25B-14	25	10-14	8	27	1.5	5
M25*1.5	M25B-16		12-16	7	30	1.5	5
M25*1.5	M25B-18		13-18	7	30	1.5	5
M27*1.5(2)	M27B-18	27	13-18	9	30	1.5(2)	2
M30*1.5(2)	M30B-18	30	13-18	9	32	1.5(2)	2

M30*1.5(2)	M30B-20		14-20	9	32	1.5(2)	2
M32*1.5(2)	M32B-22	32	15-22	9	34	1.5(2)	1
M32*1.5(2)	M32B-25		18-25	9	40	1.5(2)	1
M33*1.5(2)	M33B-22	33	15-22	9	36	1.5(2)	1
M36*1.5(2)	M36B-25	36	18-25	10	40	1.5(2)	1
M40*1.5(2)	M40B-28	40	22-28	10	45	1.5(2)	1
M40*1.5(2)	M40B-32		22-32	9	50	1.5(2)	1
M42*1.5(2)	M42B-28	42	22-28	10	45	1.5(2)	1
M48*1.5(2)	M48B-32	48	25-32	10	52	1.5(2)	5
M50*1.5(2)	M50B-32	50	25-32	10	55	1.5(2)	5
M50*1.5(2)	M50B-38		32-38	12	60	1.5(2)	5
M54*1.5(2)	M54B-38	54	32-38	12	58	1.5(2)	5
M56*1.5(2)	M56B-38	56	32-38	12	58	1.5(2)	5
M60*1.5(2)	M60B-44	60	37-44	12	64	1.5(2)	5
M63*1.5(2)	M63B-44	63	37-44	12	68	1.5(2)	5
M63*1.5(2)	M63B-53		42-53	15	78	1.5(2)	5

M64*1.5(2)	M64B-44	64	37-44	12	68	1.5(2)	5
M72*1.5(2)	M72B-52	72	42-52	15	78	1.5(2)	2
M75*1.5(2)	M75B-52	75	42-52	15	78	1.5(2)	2
M80*1.5(2)	M80B-60	80	55-60	17	88	1.5(2)	2
M88*1.5(2)	M88B-70	88	65-70	18	98	1.5(2)	1
M100*1.5(2)	M1000B-84	100	75-84	22	110	1.5(2)	1