



PN1.6pa	凸面	BQ445F-16C	BQ445F-16P	BQ445F-16CF8	BQ445F-16CF3	BQ445F-16R	BQ445F-16CF8	BQ445F-16R3
PN2.5pa	光滑面	BQ445F-25	BQ445F-25P	BQ445F-25CF8	BQ445F-25CF3	BQ445F-25R	BQ445F-25CF8	BQ445F-25R3
PN4.0pa	凹凸面	BQ445F-40	BQ445F-40P	BQ445F-40CF8	BQ445F-40CF3	BQ445F-40R	BQ445F-40CF8	BQ445F-40R3
CLASS150	凸面	BQ445F-150 ( Lb ) C	BQ445F-150 ( Lb ) P	BQ445F-150 ( Lb ) P8	BQ445F-150 ( Lb ) P3	BQ445F-150 ( Lb ) R	BQ445F-150 ( Lb ) R8	BQ445F-150 ( Lb ) R3
主要零件材料	阀体	WCB	ZG1Cr18Ni9Ti	CF8(304)	CF3(304L)	ZG18Ni12Mo2T	CF8M(316)	CF8M(316L)
	球体、阀杆	2Cr13	1Cr18Ni9Ti	0Cr18Ni9(304)	00Cr19Ni11(304L)	1Cr18Ni12Mo2Ti(16)	0Cr17Ni12Mo2(316)	0Cr17Ni12Mo2(316L)
	密封圈	聚四氟乙烯 对位聚笨						
	填料、垫圈	V型聚四氟乙烯 柔性石墨环 聚四氟乙烯片 柔性石墨复合垫						
适用工况	适用介质	重油、胶类等	硝酸腐蚀性介质	强氧化性介质	醋酸等腐蚀性介质	尿素等腐蚀性介质		
	适用温度	-28~300						
应用规范	法兰尺寸	JB79-59、SH3406、GB9113、HG20597-97 ANS1 B16.5 JIS B2212-2214						
	体试验按	GB/T13927-89 JB/T9092-99						
	其余制造规范均按本厂标准							